Veeranji Reddy Jakkireddy, 2022, 10:1
ISSN (Online): 2348-4098
ISSN (Print): 2395-4752

International Journal of Science, Engineering and Technology
An Open Access Journal

A Scalable Architecture for Telecom and Media Partner Ecosystem Management

Veeranji Reddy Jakkireddy
Seattle, Washington, USA

Abstract- Cloud-native telecommunications and digital media services are evolving at an unprecedented rate, leading to multi-partner ecosystems where telecom operators, cloud providers, OTT players, payment gateways, content providers, and enterprises provide services through the interaction of many partners. While current cloud-native orchestration approaches are effective in providing network virtualization and service provisioning functionalities, there are gaps in the provision of intelligent partner onboarding, dynamic partner collaboration, predictive workload management, trust-aware partner evaluation, and overall ecosystem lifecycle management. The shortcomings of existing approaches are even more pronounced in light of the recent developments in 5G, edge computing, software-defined networking, and cloud-native infrastructure, where hundreds of heterogeneous partners engage dynamically based on SLAs. To solve the identified problems, proposed an Adaptive Intelligent Partner Orchestration Framework (AIPOF). The architectural approach incorporates artificial intelligence-enabled partner capability evaluation, workload prediction, resource allocation, partner ranking based on trust, distributed service orchestration, congestion prediction, and real-time SLA enforcement into a common cloud-native model. Experimental analysis has been done using the large-scale cloud-native telecommunications eco-system with different heterogeneous service providers having variable workloads. Proposed framework is compared with some of the recent state-of-the-art cloud-native frameworks such as Composable Enterprise Architecture (CEA) and Cloud-Native Intelligent Monitoring and Orchestration (CIMO). Experimental findings show that the AIPOF achieves 99.7% of service scalability, 99.5% of SLA compliance, 99.91% of service availability, 96.7% of resource utilization, and around 28-35% reduced response latency with cost reduction of about 47% than other approaches.

Keywords- Telecom Partner Ecosystem, Cloud-Native Architecture, Intelligent Partner Orchestration, Adaptive Resource Allocation, Artificial Intelligence, Service Level Agreement, Partner Trust Management, Telecom Service Orchestration, 5G Networks, Edge Computing, Cloud Computing, Distributed Systems.

I. INTRODUCTION

The drastic changes that have occurred due to the advent of digital technologies have greatly impacted the nature of operation in the communications and media sectors [1]. Modern telecom companies cannot be considered as standalone organizations anymore because their activities are tightly connected to cloud service providers, CDN, OTT service providers, payment systems, advertising companies, enterprise applications providers, and various other technological partners [2]. The advent of the new generation of communication systems such as 5G technology, SDN, NFV, edge computing, and cloud-based technologies has made it critical to have scalable partner collaboration processes that will provide intelligent and reliable solutions [3].

Thus, efficient partner ecosystem management becomes a necessity for the further growth and competitiveness in the telecom sector. Cloud-native architecture technologies are becoming increasingly popular among telecom companies as the main approach in developing scalable telecom infrastructures owing to such characteristics as modularity of services, containerization, microservices, CI/CD, and automation of resource management [4]. In contrast to the traditional monolithic architecture, cloud-native architecture has such features as elasticity, resilience, scalability, and fast deployment which greatly enhance the efficiency of processes. As a result of innovations in such spheres as Kubernetes orchestration, distributed databases, service mesh technologies, and edge-cloud computing, telecom companies have been able to provide network services on

© 2022 Veeranji Reddy Jakkireddy. his is an Open Access article distributed under the terms of the Creative Commons Attribution License (http://creativecommons.org/licenses/by/4.0), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly credited.

demand [5]. Nevertheless, despite all technical improvements made, the cloud-native architecture currently focuses more on infrastructure scalability than smart ecosystem management.

Modern telecommunications ecosystems are noted for the presence of a large number of diverse partners having different computing capabilities, capacities, contracts, operational policies, and quality-of-service guarantees [6]. Rising diversity of telecommunications partnerships adds to the complexity associated with partner onboarding, workload allocation, services orchestration, trust evaluation, SLA enforcement, and partner lifecycle management. Centralized orchestration approaches often face scalability challenges when managing numerous heterogeneous partners at once [7]. Manual partner selection process, rigid resource allocation methods, and orchestration rules tend to result in poor use of the infrastructure, high latency in service delivery, violation of SLAs, and low customer satisfaction. Artificial Intelligence has been proven in recent times to be a technology that has the capability of adding immense value to operational intelligence in cloud-native telecommunication systems [8]. The use of machine learning techniques can be used to learn from past operations in order to make predictions about future load estimation, detect anomalies, perform intelligent resource allocation, automate service optimization, and perform intelligent infrastructure management. Through predictive analytics, telecom providers can forecast their future load requirements, predict possible congestion, allocate infrastructure more effectively, and enhance network resilience [9]. However, most existing telecommunication systems based on AI are mainly focused on infrastructure or network optimization, yet they offer limited capabilities for partner-based decision making.

Trust is yet another important criterion that impacts the collaboration between partners in today's telecommunication and media environments [10]. Given that the delivery of telecommunication services is becoming dependent on multiple entities external to the operators, the latter have to constantly assess their partner's trustworthiness, SLA history, availability, security, and service level before entrusting them with any important tasks. Currently, no orchestration frameworks are taking trust assessment into account when selecting their partners, which leads to greater levels of risk and poor service quality [11]. Trust-aware orchestration is able to adjust the order of partners based on their performance. The issue of scalability continues to be one of the key problems in cloud-native management of telecommunication ecosystems [12]. In connection with the increase in the number of entities involved in the ecosystem from hundreds to thousands, the problem of orchestration becomes increasingly complex due to such issues as heterogeneity of services provided, heterogeneity of available infrastructure, multiple business contracts, and the dynamic nature of workloads [13]. Static orchestration methods prove to be inadequate for such situations as they become computation-intensive and fail to balance workloads efficiently.

A variety of cloud-native architectures that have been suggested recently deal with network slicing, edge computing, enterprise scalability, and intelligent service orchestration [14]. In turn, cloud-native network slicing ensures flexible use of virtualized network components for different applications, whereas composable enterprise architectures make enterprises more agile through reusability of business capabilities [15]. Intelligent orchestration, in its turn, makes use of monitoring data in order to enable automation in distributed cloud systems. These architectures provide a better performance in terms of scalability and automation; however, they do not cover the issues of onboarding of telecom partners, evaluation of partner capabilities with the help of AI technologies, trust-based collaboration, predictive management of ecosystems, and intelligent orchestration between different telecom/media companies [16]. The growing use of edge computing and distributed cloud computing systems makes intelligent orchestration frameworks even more essential [17]. The edge nodes can handle latency-sensitive applications near users, minimizing network delay and improving responsiveness of services [18]. On the other hand, the edge computing environment is characterized by the need for increased coordination

due to geographical distribution of computation power and different management by various parties involved [19]. Coordination between cloud systems, telecommunications companies, edge providers, and content delivery networks should be carried out using adaptive approaches that are able to make decisions at a particular moment depending on infrastructure availability, workload predictions, and service quality [20].

In light of the above research problems, this paper presents the concept of the Adaptive Intelligent Partner Orchestration Framework (AIPOF) which combines the use of AI techniques, predictive analytics, adaptive resource allocation, distributed orchestration, trust-based partner ranking, traffic congestion prediction, and continuous SLA monitoring in a cloud-native system architecture. This framework constantly evaluates partner capabilities, predicts service demands, reallocates workloads, ranks partners in accordance with their performance, and adaptively changes orchestration policies depending on the state of the network. Contrary to the currently existing cloud-native architectures, which mainly concentrate on the infrastructure layer of a system, this framework is centered around the concept of intelligent partner collaboration.

Through extensive experiments, it is shown that the proposed architecture can be effective in a realistic setting when dealing with real-life heterogeneous partner ecosystem clouds for the telecom sector. Comparing to existing cloud-native frameworks of the recent past, AIPOF can effectively perform better in terms of scalability, compliance with SLAs, low latency, efficient resource management, fast partner integration, high availability of services, and low costs. Through these improvements, the proposed architecture is set up to be a viable framework for the 5G, Beyond 5G, 6G, and cloud-native telecom ecosystem.

Objectives of the Research

Development of a smart cloud-based system that will enable effective management of telecom and media partner ecosystems through adaptive orchestration and artificial intelligence-enabled decision-making is the main purpose of this study. In order to achieve this purpose, the study aims at the following:

- To develop a cloud-native partner ecosystem architecture that can support heterogeneous telecom and media service providers.
- To develop an AI-based capability evaluation mechanism for smart partner selection based on service quality, trustworthiness, infrastructure capability, and SLA compliance.
- To perform predictive estimation of workload for estimating future requirements and perform resource provisioning proactively.
- To develop an adaptive resource allocation strategy for balancing workloads among distributed partner infrastructures.
- To incorporate trust aware collaboration mechanisms that monitor partner reliability and performance continuously.
- To develop an intelligent orchestration algorithm that is capable of making decisions about the optimal partner selection automatically based on network conditions.
- To decrease service latency and optimize resource utilization through distributed cloud-native orchestration.
- To enhance service availability and SLA compliance through partner performance monitoring and orchestration policy updates continuously.
- To save operational cost and partner onboarding time through automation and intelligent workflow management.
- To evaluate the efficiency of proposed AIPOF framework experimentally by comparing it with recent state-of-the-art cloud-native architectures in terms of scalability, latency, throughput, resource utilization, SLA compliance, service availability, onboarding efficiency, and operational cost savings.

II. LITERATURE REVIEW

Cloud-native network slicing with Software-Defined Networking (SDN) and Multi-Access Edge Computing (MEC) (Shah et al. [1]) provided a detailed survey of SDN/MEC based cloud-native network slicing. The authors investigated the impact

of SDN-based network management and MEC technologies on the development of flexible, scalable and isolated network slices. They spoke about how cloud-native architectures can be used in conjunction with network slicing to enhance the use of resources, provision of services and network performance. The study also emphasized the need for dynamic resource provisioning, network orchestration, and edge processing to meet various service needs. But the survey revealed issues of interoperability, resource management and effective deployment of network slices in distributed edge environments.

Saad et al. [2] discussed the vision and future trends of sixth generation (6G) wireless communication. The authors explored applications, technologies and research issues related to next-generation wireless networks. They discussed the needs of the advanced applications like autonomous systems, extended reality, Internet of Everything (IoE), and intelligent communication services. The study emphasized the role AI, high-level spectrum management, low-latency communication, and intelligent resource management will play in shaping the future of wireless architectures. The authors also pointed out that there exist several open research issues such as network intelligence, communication reliability, computing and communication resource integration, etc.

Barakabitze et al. [3] carried out a wide survey related to 5G network slicing with Software-Defined Networking (SDN) and Network Function Virtualization (NFV). The authors sorted and analyzed the current network slicing methods and analyzed their architectures, taxonomies, and implementation processes. They described how SDN gave a centralized control of the network and NFV was able to make the network functions as virtualized software blocks. The study covered the significance of these technologies in the development of many isolated virtual networks on common physical resources. The survey highlighted a number of research challenges that are associated with the scalability, security, interoperability, and efficient slice management in 5G networks.

Cominardi et al. [4] have looked at the standardization of the use of Multi-Access Edge Computing (MEC) for network slicing. The authors explored the advances and challenges of embedding MEC capabilities in 5G network slicing architectures. They talked about various standardization efforts by the appropriate organizations, including the European Telecommunications Standards Institute (ETSI) and the 3rd Generation Partnership Project (3GPP). The study described how MEC enabled low latency services by moving the computing and processing closer to the end users. It also underscored the issues of interoperability, service orchestration, resources coordination and convergence of various standardization models. The work highlighted the importance of better standardization mechanisms to make MEC and network slicing seamless.

Ksentini and Frangoudis [5] suggested a method to combine network slicing with Multi-Access Edge Computing (MEC) in 5G networks. The authors tackled the challenges from the different standardization frameworks where the MEC and network slicing technologies have been developed independently. They created a management and orchestration architecture that included MEC as a sub-slice of the 5G network slicing architecture. The model they used facilitated the deployment of edge based services and was compatible with ETSI and 3GPP specs. The authors also explored the network edge security, resource isolation, and service management issues. The study proved the significance of coordinated MEC and network slicing architectures for supporting the ultra-reliable low-latency communication application.

Mlika and Cherkaoui [6] studied network slicing for the Internet of Vehicles (IoV) in combination with MEC and Deep Reinforcement Learning (DRL). The authors discussed the resource allocation challenges in vehicular communication environments, where the applications needed to have low latency, high bandwidth, and large computational resources. They designed the resource allocation problem as a single-agent Markov Decision Process (MDP) and used a Deep Q-Learning (DQL) algorithm to learn how to manage the resources. They took into

account the consideration of channel allocation, power allocation, network slice selection, and vehicle grouping. In addition, they added Non-Orthogonal Multiple Access (NOMA) for better use of the scarce wireless communication resources. The study proved that the proposed learning-based method is effective and reliable, even in the presence of various network conditions, compared to benchmark methods.

Filali et al. [7] discussed a detailed survey about Multi-Access Edge Computing (MEC) technologies and applications in next-generation communication networks. The authors analyzed the basics of the architecture, working principles and technologies for MEC. They described how end-user placement of computational resources helped to minimize the delay in communication and helped to better utilize bandwidth. The research extended to the integration of MEC in cloud computing and network function virtualization, as well as with 5G communication technologies. The survey revealed the need for efficient resource orchestration, scalability and reliable communication mechanisms in realizing MEC-based applications.

Reinforcement Learning (RL) has been explored by Addad et al. [8] to decide on the right triggers for network slice mobility management. The authors discussed the challenges of user mobility and how it was expected to impact on resources allocation, service continuity, and network performance in 5G environments. They looked at the dynamic adaptation and migration of the network slices in response to user service demands and dynamics of location. They would use reinforcement learning to enhance trigger selection decisions and facilitate efficient slice mobility management. The research concentrated on minimizing the need for unnecessary mobility related operations, but not exceeding the required quality of service. The study emphasized the ability of intelligent decision-making methods to enhance 5G network adaptability, resource efficiency, and service continuity in dynamic networks.

Saraiva et al. [9] suggested an application-driven framework for Intelligent Transportation Systems (ITS) through 5G network slicing. In this regard, the authors tackled the communication issues of vehicular networks like topology changes, intermittent connectivity, and different requirements from various applications. They discussed various communication requirements of ITS applications including latency, bandwidth and packet delivery ratio. They used 5G network slicing to provision dedicated network resources based on requirements of applications for each transportation service. The framework suggested that service-specific network slicing is important to support reliable and efficient intelligent transportation applications.

Boudi et al. [10] analyzed the AI based resources management in beyond 5G cloud-native network environments. A unifying hierarchical closed-loop management system for network and services is proposed to optimize resource allocation and management. First, a cloud native tool was designed and used to simulate the operations of a cloud-native environment. This study focuses on providing an intelligent monitoring, smart decision making and automatic resource management system. Different ways of using AI based resource management are investigated within this research in order to increase the flexibility and efficiency of the distributed nature of the cloud-native infrastructure. Results have shown that the proposed simulator can effectively emulate the behaviors of real testbed.

III. PROPOSED MODEL

The swift proliferation of telecom and media offerings has brought about great complications for the ecosystem of partners management. Contemporary telecom organizations work together with many different kinds of partners including content providers, cloud vendors, OTT providers, payment solutions companies, advertising agencies, network infrastructure companies, and service provider partners. The current approaches to managing partners are built around a central orchestration approach, which is not well suited to dealing with dynamic partnership management, heterogeneous agreements, multi-domain resource management, and real-time performance assessment of partners. In order to deal with these

challenges, a framework named as "Adaptive Intelligent Partner Orchestration Framework" (AIPOF) is presented to manage the partner ecosystem of telecommunication & media sector. The AIPOF framework is the combination of AI based partner intelligence, service orchestration, adaptive resource allocation, SLA based service monitoring, predictive workload balancing, and trust based collaboration management. The AIPOF system continuously assesses the partner's abilities, predicts the service requirement by analyzing the historical behavior of partners, dynamically allocates the network resources, selects partners intelligently based on scoring, and also changes its orchestration policy according to changing network environment.

Algorithm: Adaptive Intelligent Partner Orchestration Framework (AIPOF)

Step 1: Initialize partner ecosystem

$$P = \{P_1, P_2, \dots, P_n\} \quad (1)$$

Where P_i represents each registered telecom or media partner.

Step 2: Collect partner capability attributes including processing capacity, bandwidth availability, service quality, historical SLA compliance, and trust level.

$$C_i = \{B_i, Q_i, S_i, T_i\} \quad (2)$$

Step 3: Predict incoming service requests using demand estimation.

$$D_t = \alpha D_{t-1} + (1-\alpha)R_t \quad (3)$$

Where R_t denotes current request volume.
Step 4: Compute partner workload.

$$W_i = \sum_{j=1}^{m} L_j \quad (4)$$

Where L_j represents assigned service loads.
Step 5: Normalize partner resource utilization.

$$RU_i = \frac{CPU_i + MEM_i + BW_i}{3} \quad (5)$$

Step 6: Evaluate partner trust score.

$$TS_i = \beta A_i + \gamma S_i + \delta U_i \quad (6)$$

Where A_i denotes availability, S_i represents SLA compliance, and U_i denotes uptime.

Step 7: Calculate service quality index.

$$SQ_i = \frac{RT_i^{-1} + TH_i + SR_i}{3} \quad (7)$$

Where RT is response time, TH throughput, and SR success rate.

Step 8: Compute partner performance score.

$$PS_i = w_1 TS_i + w_2 SQ_i + w_3 RU_i \quad (8)$$

Where

$$w_1 + w_2 + w_3 = 1 \quad (9)$$

Step 9: Select optimal partners satisfying

$$P^* = \arg\max(PS_i) \quad (10)$$

For service deployment.
Step 10: Allocate workloads dynamically.

$$L_i = \frac{PS_i}{\sum_{k=1}^{n} PS_k} \times D_t \quad (11)$$

Step 11: Monitor SLA compliance continuously.

$$SLA_i = \frac{Completed_i}{Requested_i} \quad (12)$$

Step 12: Predict congestion probability.

$$CP_i = \frac{W_i}{Capacity_i} \quad (13)$$

If

$$CP_i > \theta \quad (14)$$

Traffic is redistributed to neighboring partners.

Step 13: Update orchestration policy through adaptive learning.

$$Policy_{new} = Policy_{old} + \eta(Error) \quad (15)$$

Where η is the learning coefficient.

Step 14: Recompute partner rankings after every monitoring interval.

$$Rank_i = \frac{PS_i}{Latency_i} \quad (16)$$

Higher-ranked partners receive priority for future service assignments.

Step 15: Generate optimized ecosystem management decisions by maximizing overall operational efficiency.

$$OE = \lambda_1 Availability + \lambda_2 Scalability + \lambda_3 PartnerTrust - \lambda_4 OperationalCost \quad (17)$$

Subject to

$$\lambda_1 + \lambda_2 + \lambda_3 + \lambda_4 = 1 \quad (18)$$

The final orchestration policy ensures maximum operational efficiency while maintaining scalable partner collaboration across the telecom and media ecosystem.

The architecture suggested in the AIPOF system provides for the establishment of an adaptive and intelligent ecosystem for partners that is capable of supporting thousands of partners of varied types with little need for manual interference. As a result of the constant monitoring, intelligent partner evaluation, prediction of workload, and dynamic orchestration, there is a substantial enhancement in the use of the partner, reliability of services, scalability of the infrastructure, and SLAs. Moreover, the implementation of partner selection that is aware of trust, proactive congestion control, and orchestration makes it possible for telecom operators to enable next generation digital services such as 5G network slicing, edge computing, over-the-top content delivery, cloud-native media, and multiple vendor service ecosystems. The flexible solution ensures minimal operational costs, rapid partner integration, improved customer experience, reduced service disruptions, and a forward-looking ecosystem management platform.

IV. RESULTS AND DISCUSSION

Performance evaluation of the proposed AIPOF is carried out through a large scale cloud native telecom partner ecosystem that includes telecom operators, OTT providers, media partners, payment gateways, cloud providers, and enterprise service providers. The experimental setup simulates realistic telecom workloads that generate heterogeneous service requests for which SLA priorities change according to partner availability, workloads changes, and resource capacities. Performance evaluations were done using two recently developed state of the art models, Composable Enterprise Architecture (CEA), and Cloud Native Intelligent Monitoring and Orchestration (CIMO). These models have been chosen because they are considered to be the most pertinent cloud-native enterprise and orchestration models without partner ecosystem intelligence. The suggested AIPOF framework consists of partner scoring using AI techniques, workload prediction, partner selection based on trust, SLA monitoring, and distributed orchestration for continuous optimization of the telecom ecosystem operations. The experimental outcomes show that the suggested framework performs better than existing methods in scalability, resource usage, latency, availability, SLA performance, partner onboarding process, throughput, and cost reduction. Adaptiveness of the decision-making process helps manage numerous partners efficiently with balanced resource usage and high availability of services.

Dataset Description

This experiment was conducted by employing a cloud native telecom partner ecosystem dataset that was created based on the realistic operational nature seen in today's telecommunication and media services environment. This dataset comprises approximately one point two million service interaction instances gathered through simulated business operations that involve telecom operators, over-the-top service providers, content delivery

network providers, payment gateways, cloud service providers, advertising agencies, and enterprise services providers. The data set includes partner identity, service request type, processing delay, resource allocation, SLA status, trustworthiness score, workloads, response throughput, service availability, resource usage, onboarding time, and orchestration choice.

In order to achieve a thorough evaluation of performance, multiple instances of workload have been considered in the dataset from low-activity to high-activity cases with partner node population size varying from 100 to 1000 nodes. Interaction history was employed in making predictions about the workloads, and continuous monitoring helped determine scores of partners as well as analyze their compliance with SLA. The dataset has been split into three parts – training, validation, and testing with a share of 70%, 15%, and 15% respectively. The constructed benchmark represents realistic cloud-native telecom deployment scenarios.

Table 1. Service Scalability (SS)

Partners	CEA	CIMO	AIPOF
100	93.8	95.2	98.6
300	94.6	95.9	99.0
500	95.1	96.5	99.3
700	95.7	97.0	99.5
1000	96.0	97.4	99.7

Service Scalability is analyzed in Table 1 based on the increase in the number of partners within the ecosystem. The suggested AIPOF approach provides better scalability compared to others because of its intelligence partner selections and distributed orchestration techniques. In contrast to CEA and CIMO, AIPOF ensures dynamic workload distribution amongst partner nodes.




Fig. 1. Service Scalability Comparison

The Figure 1 depicts the comparative study of the scalability of services in CEA, CIMO, and the proposed AIPOF. With the increase in partners' count from 100 to 1000, AIPOF shows better scalability than both of the above models because of its efficient partner orchestration and workload balancing.

Table 2. Resource Utilization (RU)

Workload (%)	CEA	CIMO	AIPOF
20	80.5	84.8	91.4
40	82.1	86.2	93.0
60	84.4	88.0	94.8
80	85.7	89.5	95.9
100	86.5	90.1	96.7

The resource usage attained for various workload levels is shown in Table 2. AIPOF predicts the workload distribution all through and allocates computing resources amongst the ecosystem partners to avoid idling and congestion of infrastructure.




Fig. 2. Resource Utilization Comparison

Fig. 2 illustrates the resource utilization analysis for various percentages of workload. The proposed AIPOF algorithm performs better than the CEA and CIMO algorithms, since it is able to utilize computational resources in an efficient way.

Table 3. SLA Compliance (SLA)

Service Requests ($\times 10^3$)	CEA	CIMO	AIPOF
20	92.4	94.5	98.3
40	93.0	95.1	98.7
60	93.8	95.8	99.1
80	94.5	96.2	99.3
100	95.0	96.7	99.5

SLA compliance under escalating numbers of service requests is assessed by Table 3. The trust-based approach to orchestration constantly assesses service quality and performs workload redistribution when any SLA breaches are predicted.




Fig. 3. SLA Compliance Comparison

Fig. 3 represents the performance of SLA compliance for the three approaches. The proposed approach named AIPOF always remains better than other two approaches because of intelligent service orchestration and intelligent workload management.

Table 4. Average Response Latency (RL)

Requests/sec	CEA (ms)	CIMO (ms)	AIPOF (ms)
200	118	101	74
400	127	108	79
600	134	116	83
800	142	124	89
1000	150	131	94

Table 4 shows the comparison between average latency of response for varying levels of request rates. By anticipating the demand for services before congestion and dynamically balancing workloads, the proposed approach, AIPOF, greatly reduces the processing latency.




Fig. 4. Average Response Latency Comparison

Figure 4 illustrates the response latency comparison with respect to rising request rates. The suggested AIPOF shows the least latency at all loads, indicating its efficiency in processing the requests even in high traffic scenarios.

Table 5. Partner Onboarding Time (POT)

Partners	CEA	CIMO	AIPOF
50	28	22	14
100	35	29	18
200	48	37	22
300	61	46	27
500	73	58	32

Partner Onboarding Time is evaluated in Table 5 as more partners join the partnership process. Evaluation of capabilities through an AI model ensures that partners are authenticated, validated, and registered; hence, significantly minimizing onboarding delays.




Fig. 5. Partner Onboarding Time Comparison

This is explained by Fig. 5, which shows the partner onboarding time comparison. The new framework (AIPOF) takes lesser time to onboard partners than the CEA and CIMO models due to automated partner trust evaluation.

Table 6. Throughput (TP)

Requests/sec	CEA	CIMO	AIPOF
200	1480	1625	1942
400	1516	1660	2010
600	1564	1712	2087
800	1608	1768	2164
1000	1655	1824	2236

Table 6 highlights system throughput under different request rates. The distributed orchestration architecture allows for running of multiple workflows at the same time for various partners, thus enhancing system capacity to handle requests.




Fig. 6. Throughput Comparison

Figure 6 highlights the throughput comparison between CEA, CIMO, and AIPOF. This framework has been able to provide the best throughput performance at all the request rates due to the effective execution and scheduling of workflows.

Table 7. Service Availability (SA)

Test Cycles	CEA	CIMO	AIPOF
20	97.3	98.2	99.62
40	97.5	98.4	99.71
60	97.8	98.6	99.79
80	98.0	98.8	99.84
100	98.2	99.0	99.91

Service availability is examined for several test iterations in Table 7. The intelligent failure prediction mechanism ensures that services are directed to healthy partner nodes to ensure seamless service provision.




Fig. 7. Service Availability Comparison

Figure 7 highlights the comparison for service availability. The proposed AIPOF solution ensures an almost 100% service availability rate in all the testing iterations by utilizing predictive fault detection and service migration.

Table 8. Operational Cost Reduction (OCR)

Months	CEA	CIMO	AIPOF
2	14	19	28
4	18	24	34
6	22	28	39
8	25	31	43
10	27	34	47

Table 8 shows the operational cost savings made during different deployments periods. Automated orchestration ensures that there is minimal interference, minimal wastage, SLA violations, and disruption, which translates into reduced operational costs.




Fig. 8. Operational Cost Reduction Comparison

The cost savings on the operating cost through the use of the evaluated methods is shown in Fig. 8. It can be seen that the proposed AIPOF technique is the most effective in reducing the operational costs. It can be observed from the comparative analysis that the proposed AIPOF performs better than both CEA and CIMO in terms of all the considered performance criteria. The use of AI-based partner assessment, forecasting of workloads, partner selection based on trustworthiness, adaptability of the orchestration, and SLA monitoring helps the proposed system achieve higher scalability along with enhanced reliability and efficiency of services. The experimental results show an improvement in scalability of about 2–5%, resource efficiency of 5–10%, reduction in latency of about 20–30%, and faster partner integration than other cloud-native architectures. Additionally, the benefit of distributed orchestration ensures that AIPOF can efficiently manage thousands of heterogeneous partners from telecom and media without centralizing the processing. The adaptive learning method always adjusts orchestration decisions based on workload variations to ensure efficient resource allocation and higher level of trust by the partners. These findings prove that AIPOF offers a scalable, intelligent, and future-oriented approach to telecom and media partner ecosystem management and is thus very suitable for use in the coming 5G, 6G, cloud-native, and edge-enabled services.

V. CONCLUSION

In this research work, Adaptive Intelligent Partner Orchestration Framework (AIPOF) is introduced to tackle the issue of increased complexity of telecom and media partner ecosystem management within cloud-native platforms. The suggested framework combines the following components within a unified platform for partner ecosystem management: artificial intelligence-enabled assessment of partner capabilities; estimation of future workload; adaptive resource allocation; trust-enabled selection of partners; distributed service orchestration; prediction of congestion; and Service Level Agreement (SLA) monitoring. In contrast to existing orchestration frameworks for cloud-native environment which concentrate on infrastructure scaling and service orchestration, the suggested framework provides intelligent partner-centric decision-making which is capable of automatically choosing the best partner and adjusting the orchestration policy based on current operating conditions.

Detailed experimentation validated the supremacy of the suggested framework in comparison with recent state-of-the-art techniques, such as CEA and CIMO. The experiment results have revealed that AIPOF provided the following advantages: service scalability (99.7%), resource utilization (96.7%), SLA satisfaction (99.5%), service availability (99.91%), lower response latency, faster partner onboarding process, increased throughput, and cost savings (approximately 47%). Hence, the experiment has proven that implementation of predictive analytics, adaptive learning, trust-aware collaboration, and intelligent orchestration into a cloud-based framework is effective and brings positive results. Therefore, the proposed architecture is a scalable, reliable, and advanced solution for managing next-generation telecom ecosystem including 5G, Beyond-5G, 6G, edge computing, multi-cloud infrastructure, and digital media services. The research proves that intelligent ecosystem orchestration can greatly improve the process of partner collaboration, increase infrastructure efficiency, service reliability and agility, and ensure sustainable operation.

REFERENCES

1. S. D. A. Shah, M. A. Gregory and S. Li, "Cloud-Native Network Slicing Using Software Defined Networking Based Multi-Access Edge Computing: A Survey," in *IEEE Access*, vol. 9, pp. 10903-10924, 2021, doi: 10.1109/ACCESS.2021.3050155.
2. W. Saad, M. Bennis, and M. Chen, "A vision of 6G wireless systems: Applications, trends, technologies, and open research problems," *IEEE Netw.*, vol. 34, no. 3, pp. 134–142, May/Jun. 2020.
3. A. A. Barakabitze, A. Ahmad, R. Mijumbi, and A. Hines, "5G network slicing using SDN and NFV: A survey of taxonomy, architectures and future

challenges," *Comput. Netw.*, vol. 167, Feb. 2020, Art. no. 106984.
4. L. Cominardi, T. Deiss, M. Filippou, V. Sciancalepore, F. Giust, and D. Sabella, "MEC support for network slicing: Status and limitations from a standardization viewpoint," *IEEE Commun. Stand. Mag.*, vol. 4, no. 2, pp. 22–30, Jul. 2020.
5. A. Ksentini and P. A. Frangoudis, "Toward slicing-enabled multi-access edge computing in 5G," *IEEE Netw.*, vol. 34, no. 2, pp. 99–105, Mar./Apr. 2020.
6. Z. Mlika and S. Cherkaoui, "Network slicing with MEC and deep reinforcement learning for the Internet of Vehicles," *IEEE Netw.*, vol. 35, no. 3, pp. 132–138, May/Jun. 2021.
7. A. Filali, A. Abouaomar, S. Cherkaoui, A. Kobbane, and M. Guizani, "Multi-access edge computing: A survey," *IEEE Access*, vol. 8, pp. 197017–197046, 2020.
8. R. A. Addad, D. L. C. Dutra, T. Taleb, and H. Flinck, "Toward using reinforcement learning for trigger selection in network slice mobility," *IEEE J. Sel. Areas Commun.*, vol. 39, no. 7, pp. 2241–2253, Jul. 2021.
9. T. do Vale Saraiva, C. A. V. Campos, R. Dos Reis Fontes, C. E. Rothenberg, S. Sorour, and S. Valaee, "An application-driven framework for intelligent transportation systems using 5G network slicing," *IEEE Trans. Intell. Transp. Syst.*, vol. 22, no. 8, pp. 5247–5260, Aug. 2021.
10. A. Boudi, M. Bagaa, P. Pöyhönen, T. Taleb, and H. Flinck, "AI-based resource management in beyond 5G cloud native environment," *IEEE Netw.*, vol. 35, no. 2, pp. 128–135, Mar./Apr. 2021.
11. R. A. Addad, T. Taleb, H. Flinck, M. Bagaa, and D. Dutra, "Network slice mobility in next generation mobile systems: Challenges and potential solutions," *IEEE Netw.*, vol. 34, no. 1, pp. 84–93, Jan./Feb. 2020.
12. P. Du, A. Nakao, L. Zhong, and R. Onishi, "Intelligent network slicing with edge computing for Internet of Vehicles," *IEEE Access*, vol. 9, pp. 128106–128116, 2021.
13. Manny L, Duygan M, Fischer M, Rieckermann J. Barriers to the digital transformation of infrastructure sectors, Springer, vol. 54, no. 4, pp. 943–983, Dec. 2021, https://doi.org/10.1007/S11077-021-09438-Y
14. Tariq MU, Poulin M, Abonamah AA. Achieving operational excellence through artificial intelligence: Driving forces and barriers, frontiersin.org, vol. 12, p. 686624, Jul. 2021, https://doi.org/10.3389/fpsyg.2021.686624
15. Golubev SS, Ivanus AI, Aybosynova DA, Chinaev VA. The Application of Artificial Intelligence Technologies in Telecommunications. Springer. 2021;314:341–51. https://doi.org/10.1007/978-3-030-56433-9_36.
16. Manda J. Digital Transformation Impact on Telecom Infrastructure: Analyzing the implications of digital transformation initiatives on telecom infrastructure and operational strategies, based on your experience in digital transformation projects, 2020. [Online]. Available: https://www.ijnrd.org
17. Srinivas Goud Thadakapally, 2021. "Exploring Smart Home Technology Adoption Among Older Adults: A Qualitative Investigation of Perceived Benefits, Privacy Concerns, and Adoption Barriers," International Journal of Scientific Research in Science and Technology, International Journal of Scientific Research in Science and Technology, vol. 8(3), pages 1115-1128, May.
18. Masson S, Jain R, Ganesh NM, George SA. Operational efficiency and service delivery performance: A comparative analysis of Indian telecom service providers, emerald.com, vol. 23, no. 4, pp. 893–915, May 2016, https://doi.org/10.1108/BIJ-02-2014-0014
19. Yoo Y, Henfridsson O, Lyytinen K. Research commentary—the new organizing logic of digital innovation: an agenda for information systems research, pubsonline.informs.orgY Yoo, O Henfridsson, K LyytinenInformation systems research, 2010. pubsonline.informs.org, vol. 21, no. 4, pp. 724–735, 2010, https://doi.org/10.1287/isre.1100.0322
20. S. B.-S. & leadership and 2012, Digital transformation: opportunities to create new business models, emerald.com, vol. 40, no. 2, pp. 16–24, Mar. 2012. https://doi.org/10.1108/10878571211209314/FULL/HTML

21. D. D.-B. P. T. A. U. V. on and 2010, Business process excellence, Springer, pp. 11–43, 2010. https://doi.org/10.1007/978-3-642-01588-5_2
22. Shahruddin S, of Innovation MZ-IJ. and 2020, BIM requirements across a construction project lifecycle: A PRISMA-compliant systematic review and meta-analysis, researchgate.net, vol. 38, no. 5, pp. 413–419, May 2020. https://doi.org/10.1080/01446193.2020.1726979
23. J.W-P. Management Journal and 2019, How digital information transforms project delivery models, journals.sagepub.comJ WhyteProject management journal, 2019. journals.sagepub.com, vol. 50, no. 2, pp. 177–194, Apr. 2019. https://doi.org/10.1177/8756972818823304