Dr. Suchita Walke, 2026, 14:2
ISSN (Online): 2348-4098
ISSN (Print): 2395-4752

International Journal of Science, Engineering and Technology
An Open Access Journal

# Human Following Robot Using Arduino Uno

**Dr. Suchita Walke, Sojal Patil , Yash Gadge , Sudarshan Shedge**
Computer Engineering Pillai HOC College of Engineering and Technology Rasayani, India

**Abstract- Nowadays, Technology Advances So Rapidly That Robots Start to Emerge Not Just in Factories, But in Our Daily Lives Helping Us With Big And Small Things. For This Project, We Were Excited to Build Something Helpful and Entertaining: A Human-Following Robot. It Is a Small, Moving Robot Built Out of Low-Budget and Beginner- Friendly Materials Like an Arduino Uno, Ultrasonic Sensors, And A Motor Driver. The Idea Is Simple to Grasp the Robot Follows A Person By Detecting Their Movement And Staying A Safe Distance Behind. This Is How It Works: The Robot Has Ultrasonic Sensors That Send Out Sound Waves. When The Waves Reflect Off Something, The Robot Calculates How Far Away That Something Is. With Two Or More Sensors, It Can Even Calculate The Direction The Person Is Heading. The Arduino Does That Entire Math and Tells the Motors How to Go So The Robot Can Coast Along Smoothly Without Running Into Things. This Robot's Design Is Versatile and Has Numerous Applications In Home Life. It Can Be an Intelligent Shopping Cart That Accompanies You In A Supermarket, A Home Robot That Assists The Elderly, Or A Warehouse Robot That Transports Items From One Point To Another. And as The Design Is Low-Cost and Minimalistic, It Is Perfect For Hobbyists Who Want To Play With Robotics, Sensors, And Embedded Systems. Once The First Version Is Up and Running, There's Plenty Of Scope For Enhancement Such As Incorporating A Camera For Video Tracking, Incorporating Ai To Make It Intelligent, Or Networking It For Net-Based Monitoring. For Hobbyists and Students, It's An Excellent Hands-On Exercise To Learn How Software And Hardware Interface, And A Precursor To Building Sophisticated and Intelligent Robots In The Future.**

**Keywords: Human Following Robot, Arduino Uno, Ultrasonic Sensors, Motor Driver Module, Real-Time Sensor Integration, Smart Technology, Autonomous Navigation, Obstacle Detection, Iot, Ai In Robotics**

## I. INTRODUCTION

With the growing use of robots in everyday life, there is an increasing need for machines that can move and work alongside humans safely. One such application is a human-following robot, which is designed to automatically detect a person and follow them while

maintaining a safe distance. These robots are useful in many areas such as personal assistance, hospitals, warehouses, and service industries, where they can reduce human effort and improve efficiency. However, developing a robot that can accurately follow a human in real time is not simple, as it must respond continuously to human movement and environmental changes.

Most traditional robotic systems depend on fixed paths or manual control, which makes them unsuitable for dynamic environments. These methods are slow, inflexible, and cannot adapt to sudden changes in human position. For a robot to follow a human effectively, it must be able to sense distance, make quick decisions, and move smoothly without collisions. If proper sensing and control mechanisms are not used, the robot may behave unpredictably, lose the target, or create safety risks. Therefore, an automated and well-structured approach is required to achieve reliable human-following behavior.

Human-following robots that exist today generally fall into two categories. The first type uses simple distance- based control, where the robot moves forward or backward depending on how close the person is. While these systems are easy to build, they often struggle in real- world conditions and lack accuracy. The second type includes more advanced robots that use multiple sensors and complex algorithms for better tracking and navigation. Although these systems perform well, they are expensive and difficult to implement, especially for small- scale or academic projects.

© 2026 Dr. Suchita Walke .This is an Open Access article distributed under the terms of the Creative Commons Attribution License (http://creativecommons.org/licenses/by/4.0), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly credited.

To overcome these challenges, this project presents a human-following robot developed using an Arduino microcontroller and an ultrasonic sensor. The robot continuously monitors the distance between itself and the human target and adjusts its movement to maintain a safe and steady following distance. The control logic is designed to be simple yet effective, allowing the robot to respond quickly to changes in position. By using easily available components and straightforward programming, the proposed system offers a low-cost and practical solution for human-following applications, making it suitable for educational and real-world use.

## II. LITERATURE SURVEY

Human-following robotic systems have gained attention in recent years, particularly in low-cost mobile robots used for assistance and automation. Early studies focused on simple distance-based tracking using sensors like ultrasonic and infrared to detect human presence and maintain a fixed following distance. Ultrasonic sensors are widely preferred due to their low cost, ease of implementation, and reliable short-range distance measurement. Microcontroller platforms such as Arduino are commonly used because they support real-time processing and flexible control logic.

More advanced systems combine multiple sensors and control techniques to improve tracking accuracy, movement stability, and safety through obstacle detection and avoidance. Although these approaches enhance performance, they also increase system complexity and cost. Therefore, many researchers continue to focus on simplified designs that offer a balance between accuracy, affordability, and ease of implementation. Overall, existing studies show that Arduino-based human-following robots using ultrasonic sensors provide an effective and practical solution for basic human–robot interaction.

"Human Following Robot Using Arduino" – R. Umbare, A. Budhodkar (2025) [1]: This paper presents a human-following robot developed using Arduino Uno, ultrasonic sensors, and infrared sensors to track a human target. The system measures the distance between the robot and the person using ultrasonic sensing and adjusts motor movement accordingly. IR sensors are employed to determine directional changes of the target. The proposed approach is cost-effective and suitable for educational purposes. However, the system is limited to indoor environments and lacks advanced obstacle avoidance and adaptive decision-making capabilities. The proposed human-following robot enhances this approach by integrating optimized sensor logic for smoother tracking and improved movement stability.

"A Study of Ultrasonic Sensor Capability in Human Following Robot System" – W. W. Tai, B.Lits. S.A.A. Shukor, M.A. Markom (2019)[2]: This research analyzes the performance of ultrasonic sensors in human-following robotic systems. The authors evaluate distance accuracy, response time, and reliability under varying conditions. The study demonstrates that ultrasonic sensors are effective for short-range human tracking but are sensitive to surface reflectivity and environmental noise. While the paper focuses on sensor evaluation, it does not implement a complete robotic following system. The proposed system builds upon these findings by combining ultrasonic sensing with IR sensors to improve directional accuracy and real-time responsiveness.

"Human-Following Mobile Robot in a Distributed Intelligent Sensor Network" – K. Morioka, J.H. Lee ,H. Hashimoto(2004)[3]: This paper introduces a human-following mobile robot using a distributed sensor network for tracking human movement. The system employs multiple sensors to improve tracking accuracy and reduce error caused by occlusion. Although the approach provides high reliability, it requires complex sensor infrastructure and high computational resources, making it unsuitable for low-cost implementations. In contrast, the proposed Arduino-based human-following robot focuses on simplicity and affordability while maintaining reliable tracking performance.

"Human Following Robot Based on Motion Sensing Technology" – S. S. Patil, R. S. Patil (2020) [4]: The authors propose a motion-sensing-based human-

following robot that detects human movement patterns using proximity sensors. The robot follows the detected motion by adjusting motor speed and direction. While the system demonstrates effective human detection, it struggles with false detections and lacks precise distance control. The proposed system addresses these limitations by using ultrasonic sensors for accurate distance measurement and IR sensors for directional tracking.

"Design and Implementation of Human Following Robot with Obstacle Avoidance" – A. Kumar, P.Singh(2021)[5]: This paper presents a human-following robot integrated with obstacle avoidance functionality using ultrasonic sensors. The system dynamically switches between following mode and obstacle avoidance mode. Although effective, the design increases system complexity and power consumption. The proposed human-following robot adopts a simplified control strategy that balances tracking accuracy and obstacle avoidance while maintaining low hardware complexity

## III. METHODOLOGY

The methodology of the proposed Human Detection and Motion Control System follows a structured multi-step approach, starting from sensing the human presence to actuating motor movement based on processed distance data. The system is divided into sensing, processing, and actuation layers to ensure modular and efficient operation.

**System Initialization and Power Supply Setup**
The system begins operation when the battery pack supplies power to all hardware components, including the Arduino Uno, ultrasonic sensor, motor driver, DC motors, and optional OLED display. The Arduino initializes the input and output pins, configures communication protocols, and prepares the system for continuous sensing and control operations.

**Ultrasonic Sensor Activation**
After initialization, the Arduino triggers the HC-SR04 ultrasonic sensor to emit high-frequency ultrasonic sound waves into the surrounding environment. These sound waves propagate forward from the sensor toward potential human targets.

**Human Detection and Echo Reception**
When the transmitted ultrasonic waves encounter a human or any obstacle, they are reflected back toward the sensor. The echo pin of the ultrasonic sensor receives the reflected signal, and the total travel time of the wave is captured by the Arduino for further processing.

**Distance Measurement and Interpretation**
The Arduino calculates the distance between the sensor and the detected human by using the received echo time and the known speed of sound in air. This calculated distance value represents the real-time proximity of the human target relative to the system.

**Processing and Decision Logic Execution**
The calculated distance data is processed by the Arduino Uno, which compares the measured value against predefined threshold distances. Based on this comparison, the microcontroller determines the appropriate action such as moving forward, stopping, or changing direction, ensuring logical and controlled behavior of the system.

**Motor Control Signal Generation**
Once a decision is made, the Arduino generates appropriate digital and PWM control signals corresponding to motor speed and direction. These signals serve as command inputs for the motor driver module.

**Actuation Through Motor Driver**
The motor driver module receives the control signals from the Arduino and amplifies them to drive the DC gear motors. Based on the received commands, the left and right motors rotate in the required direction and speed, resulting in physical movement of the system

**Status Display and Debug Output (Optional)**
An optional OLED display provides real-time visual feedback by displaying distance values, system status, or debugging information. Communication between the Arduino and the display is handled

using I2C or SPI protocols, enabling effective system monitoring.

**Continuous Monitoring and Loop Execution**

The entire methodology operates in a continuous loop, where sensing, processing, and actuation are repeatedly performed. This continuous execution allows the system to dynamically respond to changes in human position and maintain accurate, real-time motion control.




Figure.1 System Architecture

## IV. RESULT ANALYSIS

**Side View of the Human-Following Robot**



The side-view image confirms successful mechanical integration of the Arduino UNO, motor driver, battery pack, and DC motors on a compact sun board chassis. The low centre of gravity achieved by placing the battery pack centrally improves stability during motion. Proper wheel alignment and equal load distribution across all four TT gear motors ensure smooth forward movement and effective turning. The compact wiring layout minimizes signal interference and enhances reliability during continuous operation.

**Rear View Showing Power System Integration**



The rear-view image demonstrates stable power supply integration using Li-ion batteries, a battery holder, and a DC power switch. The use of a dedicated power switch allows safe startup and shutdown of the robot. Battery placement at the rear balances the sensor assembly at the front, reducing tilting during acceleration or deceleration. The motor driver receives consistent voltage, ensuring uniform motor speed under load.

**Front View with Ultrasonic Sensor Module**



The ultrasonic sensor mounted at the front successfully detects the human target within the predefined distance range. The elevated sensor position improves line-of-sight distance measurement and reduces false readings from the ground. Real-time distance data enables the robot to dynamically adjust its speed and direction, forming the core of the human-following mechanism. The sensor alignment ensures accurate detection of forward motion and directional changes.

**Top View of Complete System Layout**



The top-view image validates the complete hardware layout, including Arduino UNO, motor driver module, power regulation unit, and sensor connections. Logical placement of components reduces wiring complexity and power loss. The Arduino effectively processes sensor inputs and sends control signals to the motor driver with minimal delay. This configuration supports reliable real-time decision-making and ensures consistent robot response.

**Overall System in Operational Environment**

The robot successfully follows a moving human in an indoor environment while maintaining a safe distance and avoiding obstacles. Experimental observation shows smooth following behaviour with minimal jerks or delays. The combination of ultrasonic and infrared sensors improves detection accuracy under varying lighting conditions. The system demonstrates robustness, low-cost implementation, and suitability for indoor assistance and material-handling applications.

## V. SCOPE OF RESEARCH

The scope of this research focuses on the design and development of a human detection and motion control system using an ultrasonic sensing mechanism and a microcontroller-based control unit. The system aims to detect the presence and distance of a human target using ultrasonic sound waves and to process this information in real time for intelligent motion control. The project integrates a sensing layer for distance measurement, a processing layer using an Arduino Uno microcontroller for decision-making, and an actuation layer consisting of a motor driver and DC gear motors for physical movement. The scope further includes the implementation of real- time distance calculation, threshold-based decision logic, and motor control using PWM and digital signals. An optional display unit is incorporated to provide system status, distance readings, and debugging information for effective monitoring. The research emphasizes a modular, low-cost, and energy-efficient design that can be easily implemented using readily available hardware components.

This system is intended to demonstrate practical applications of embedded systems, robotics, and automation, such as human-following robots, obstacle- aware vehicles, and assistive robotic platforms. The scope is limited to short-range human detection using ultrasonic sensors and does not include advanced vision-based recognition or machine learning techniques. Overall, the project aims to provide a reliable, scalable, and beginner-friendly framework for real-time human detection and motion control in embedded applications.

## VI. CONCLUSION

The Human-Following Robot developed using an Arduino UNO and ultrasonic sensors demonstrates an effective low-cost approach to autonomous

human-assisted navigation. The system successfully detects and tracks a human target by continuously measuring distance and executing rule-based motion control to maintain a safe following range. Integration of ultrasonic and infrared sensors enables reliable obstacle detection, ensuring smooth movement and collision avoidance in indoor environments. Experimental results confirm that the robot responds accurately to changes in human position by adjusting speed and direction in real time. The use of a simple yet efficient control algorithm ensures stable operation with minimal computational overhead, making the system suitable for educational, domestic, and industrial assistance applications. The modular hardware design allows easy expansion and maintenance while keeping overall system cost low. Overall, this project bridges the gap between theoretical embedded systems knowledge and practical autonomous robotics implementation. It demonstrates that reliable human- following behaviour can be achieved using inexpensive components and straightforward control logic. Future enhancements may include camera-based vision tracking, machine learning–based target identification, IoT-enabled monitoring, and advanced path-planning algorithms to improve accuracy, adaptability, and real-world usability.

## VII. FUTURE SCOPE

The current Human-Following Robot can be further enhanced by integrating advanced sensing and intelligence techniques. Camera-based vision systems and machine learning algorithms can be incorporated to improve human identification accuracy and eliminate false target detection. IoT integration can enable real-time monitoring, remote control, and data logging through cloud platforms. GPS and mapping modules may be added for outdoor navigation and path planning. Additionally, increasing payload capacity and optimizing motor control can make the system suitable for industrial material handling and healthcare assistance applications. These enhancements will improve system adaptability, intelligence, and real- world usability.

## VIII. DISCUSSION

The implementation of the Human-Following Robot demonstrates the effectiveness of using low-cost components such as Arduino UNO and ultrasonic sensors to achieve autonomous following behaviour. The system successfully detects a human target, maintains a safe distance, and adjusts movement in real time based on sensor feedback. Rule-based motion control ensures smooth navigation, obstacle avoidance, and stable operation in indoor environments. The modular hardware design simplifies system integration and allows easy scalability. Experimental observations indicate reliable performance, minimal response delay, and consistent tracking accuracy. Overall, the project validates that efficient human-following robots can be developed using simple control logic, making the solution practical for educational, domestic, and industrial assistance applications.

### ACKNOWLEDGMENT

We would like to express our sincere gratitude to Ms. Suchita Walke for their valuable guidance, continuous support, and encouragement throughout the development of this project. Their technical insights and constructive feedback played a significant role in improving the design and implementation of the Human-Following Robot. We also thank our institution for providing the necessary facilities and resources required to complete this project successfully. Finally, we extend our appreciation to all those who supported us directly or indirectly during the course of this work.

## REFERENCES

1. Human Following Robot Using Arduino – R. Umbare, A. Budhodkar (2025)
2. A Study of Ultrasonic Sensor Capability in Human Following Robot System – W. W. Tai, B.Lits. S.A.A. Shukor,M.A.Markom(2019)
3. Human-Following Mobile Robot in a Distributed Intelligent Sensor Network– K. Morioka,J.H.Lee,H.Hashimoto(2004)

4. Human Following Robot Based on Motion Sensing Technology – S. S. Patil, R. S. Patil (2020)
5. Design and Implementation of Human Following Robot with Obstacle Avoidance – A. Kumar, P.Singh(2021)
6. K. Morioka, J.-H. Lee, and H. Hashimoto, "Human-following mobile robot in a distributed intelligent sensor network," IEEE Trans. Ind. Electron., vol.51, no.1, pp. 229–237, Feb. 2004.
7. H. Takemori, N. Zentaro, and H. Mizoguchi, "Development of vision based person following module for mobile robots in/ out door environment," in Proc. 2009 IEEE International Conference on Robotics and Biomimetics (ROBIO), 2009, pp. 1675–1680.