

AI-Powered Adaptive Frequency Antenna for Seamless Wireless Communication

Mr. Sunil Kondiram Janrao¹, Mr. Hemraj Tukaram Gangurde², Miss. Jadhav Savita Yogiraj³,
Miss. Rupali Shravan Salmuthe⁴, Dr. Prashant Thakare⁵

^{1,2,3,4}UG Student, Department of Electronics and telecommunication Sandip institute of technology and
research center Mahiravani Nashik

⁵Professor, Department of Electronics and telecommunication Sandip institute of technology and
research center Mahiravani Nashik

Abstract- Wireless communication systems today demand high reliability and adaptability as signal quality constantly varies due to interference, environmental obstacles, and user mobility. However, conventional fixed-frequency antennas lack the ability to adjust to such dynamic conditions, resulting in signal degradation, reduced coverage, and unstable communication. To address this limitation, this project proposes an AI-Powered Adaptive Frequency Antenna System capable of intelligently switching between multiple microstrip patch antennas tuned to 2.4 GHz, 3.7 GHz, and 5.5 GHz. A Software Defined Radio (SDR) module is used to capture real-time signal data, while a Raspberry Pi processes key parameters such as Received Signal Strength Indicator (RSSI) and Signal-to-Noise Ratio (SNR) using AI-based decision-making algorithms. Based on the analysis, the system automatically selects and activates the antenna that provides the best communication performance through a relay or RF switch. This adaptive approach ensures stable connectivity, improved signal quality, optimized bandwidth usage, and energy-efficient operation. The proposed system offers a low-cost, scalable, and intelligent solution suitable for applications such as IoT networks, smart infrastructure, mobile communication, and next-generation wireless systems.

Keywords: AI-based Antenna, Adaptive Frequency Switching, Software Defined Radio (SDR), Raspberry Pi, Microstrip Patch Antenna, RSSI, SNR, Wireless Communication, Smart Antenna System, Real-Time Signal Processing.

I. INTRODUCTION

Wireless communication has become an essential part of modern technology, supporting applications such as mobile networks, IoT devices, satellite communication, and smart city infrastructures. In these systems, antennas play a major role in transmitting and receiving electromagnetic signals efficiently. However, most conventional antennas are fixed-frequency types, meaning they operate only at a single, pre-defined frequency. These antennas cannot adjust themselves in response to changing signal conditions such as interference, environmental obstacles, or user mobility. As a result, users often experience signal drops, reduced data rates, and poor connectivity.

To overcome these challenges, the concept of adaptive frequency antennas has been introduced. These antennas are capable of automatically

switching or tuning their operating frequency based on real-time communication conditions. When combined with Artificial Intelligence (AI) and Software Defined Radio (SDR), the system gains the ability to continuously analyse signal quality and intelligently choose the most suitable frequency band.

The proposed project, titled "AI-Powered Adaptive Frequency Antenna for Seamless Wireless Communication," focuses on developing a multi-band microstrip patch antenna system operating at 2.4 GHz, 3.7 GHz, and 5.5 GHz. An SDR module is used to capture the wireless signal, while a Raspberry Pi processes real-time indicators such as Signal-to-Noise Ratio (SNR) and Received Signal Strength Indicator (RSSI) using AI-based decision algorithms. Based on this analysis, the system automatically switches to the antenna with the best performance, ensuring stable and efficient communication.

II. RELATED WORKS

Wireless communication has evolved significantly over the years, and several researchers have contributed to improving antenna performance, frequency agility, and signal adaptability. However, many of the existing systems still face limitations in dynamic environments. This chapter presents a review of previous research works related to adaptive antennas, AI-based antenna control, and Software Defined Radio applications.

Adaptive Antenna Systems

In earlier studies, researchers focused on designing reconfigurable antennas using mechanical, electrical, and material-based tuning methods. Varactor diodes, PIN diodes, MEMS switches, and metamaterials were commonly used to change the resonant frequency. While these methods successfully enabled frequency switching, they lacked intelligence and real-time decision-making capability. Manual or pre-programmed tuning was required, which is not suitable for highly dynamic wireless environments.

Software Defined Radio (SDR) in Frequency Control

Software Defined Radio (SDR) technology has allowed radio communication components to be controlled via software instead of hardware. Research shows that SDR can dynamically analyse and modify radio parameters such as modulation, filtering, and frequency allocation. However, most SDR-based systems still depend on manual configuration or static signal thresholds, lacking the ability to automatically optimize antenna selection or performance.

AI-Based Wireless Communication Optimization

In recent years, AI methods such as machine learning and deep learning have been applied to improve network performance. Studies indicate that AI can effectively predict channel conditions, detect interference, and optimize communication parameters. However, most existing AI applications are focused on network traffic and routing, rather than physical antenna-level optimization.

III. LITERATURE REVIEW

The development of intelligent and adaptive antenna systems has gained considerable attention in recent years due to the growing demand for reliable and high-quality wireless communication. This chapter presents a review of research works that explore reconfigurable antennas, Software Defined Radio (SDR)-based signal monitoring, and Artificial Intelligence (AI) for dynamic wireless optimization.

AI-Based Adaptive Antenna Systems

Researchers have investigated various methods to achieve frequency agility in antennas. Many studies highlight the importance of dynamic frequency switching to cope with environmental changes. Y. Li et al. (2022) demonstrated that AI algorithms can be used to analyse channel states and optimize communication parameters dynamically, improving signal stability and bandwidth utilization. However, their approach focused primarily on software-level parameter adjustment and did not include hardware antenna switching.

Similarly, S. Ahmed and M. Rizwan (2021) proposed a machine-learning-based prediction model for channel selection in 5G networks. Their system successfully predicted optimal channels under varying noise conditions. However, the implementation was limited to simulation-based environments and lacked integration with physical antenna hardware.

Reconfigurable Microstrip Patch Antennas

Microstrip patch antennas are widely used for communication applications due to their simple structure, low weight, and ease of fabrication. Kumar and Singh (2020) designed a tunable microstrip patch antenna using varactor diodes for multi-frequency operation. While the design allowed switching between two frequency bands, the switching required manual control and did not support automatic adaptation.

Another study by Patel and Mehta (2019) introduced a reconfigurable antenna using PIN diode switching to enable multi-band operation. Although the antenna achieved good frequency coverage, the

switching mechanism lacked intelligent real-time decision-making based on signal conditions.

IV. ANALYSIS OF ANTENNA DESIGN

Antenna Design

In this project, three distinct microstrip patch antennas were designed to operate at 2.4 GHz, 3.7 GHz, and 5.5 GHz. These frequencies are selected based on their importance in modern wireless communication standards such as Wi-Fi, 5G, and mid-band communications. Instead of employing a single reconfigurable or wideband antenna, the system uses three independently designed antennas, each optimized to perform efficiently at its target frequency. These antennas are integrated into the overall system using a relay switching mechanism, controlled by a Raspberry Pi, which activates the appropriate antenna based on signal conditions and machine learning model predictions.

Each antenna was designed using the CST simulation tool, with an emphasis on achieving compactness, strong impedance matching, and desirable radiation characteristics. To improve performance, slots were introduced in the patch structure of each antenna. These slots were strategically placed to influence the surface current distribution, allowing for fine-tuning of the resonance frequency, enhanced gain, and reduced return loss.

Mathematical Modelling

The basic dimensions of the microstrip patch antennas were determined using conventional antenna design equations, considering the dielectric properties of the substrate and the desired operating frequencies. The width W and effective length L_{eff} of the patch were calculated using the following standard equations:

$$W = \frac{c}{2f_0 \sqrt{\frac{\epsilon_r + 1}{2}}} \dots(1)$$

$$L = L_{eff} - 2\Delta L$$

$$\text{Where } L_{eff} = \frac{c}{2f_0 \sqrt{\epsilon_{reff}}} \dots(2)$$

where W is width and L is length of the patch of intended antenna. f_0 depicts the frequency of

operation, ϵ_r shows relative dielectric constant and ΔL is fringing field effect, which is basically a change in length, it is calculated by using following equation:

$$\Delta L = 0.412h \frac{(\epsilon_{reff} + 0.3) \left(\frac{W}{h} + 0.264\right)}{(\epsilon_{reff} - 0.258) \left(\frac{W}{h} + 0.8\right)} \dots(3)$$

While ϵ_{reff} is calculated as follow as:

$$\epsilon_{reff} = \frac{\epsilon_r + 1}{2} + \frac{\epsilon_r - 1}{2} \left[1 + 12 \frac{h}{W} \right]^{\frac{1}{2}} \dots(4)$$

where H_s is height of the substrate and W_s is width of the substrate while ϵ_{reff} denoted the effective permittivity.

These calculations provided initial dimensions for each antenna, which were then fine-tuned in CST through iterative simulation to optimize return loss, VSWR, and gain. The slot geometries were adjusted to shift the resonance precisely to the required band and improve impedance matching without increasing the overall footprint.

Simulated Results

The simulated performance of the designed antennas confirms their effective operation across the intended frequency bands. The 2.4 GHz antenna achieved a return loss of -28.45 dB, indicating strong resonance with minimal reflection, and exhibited a VSWR of 1.1, suggesting excellent impedance matching. The 3.6 GHz antenna demonstrated superior performance with a return loss of -17.20 dB and a corresponding VSWR of 1.3, confirming efficient energy transfer and well-tuned slot dimensions. For the 5.6 GHz antenna, the simulated return loss was -21.40 dB, with a VSWR of 1.7, indicating stable resonance and good impedance characteristics. These results validate the suitability of the antenna designs for their respective frequency bands and confirm the accuracy of the simulation and optimization process. again, confirming proper tuning and impedance match. In addition to S-parameters, the gain of the antennas was also studied.




Fig 1: 2.4 GHz Simulated Gain Plot 3D

Figure 1 presents the 3D gain plot for the 2.4 GHz antenna, revealing a peak gain of 6.91 dB, with a relatively symmetrical radiation pattern




Fig 2: 3.6 GHz Simulated Gain Plot 3D

Figure 2 shows the gain plot of the 3.7 GHz antenna, which achieves a maximum gain of 6.88 dB, highlighting strong directivity and radiated power concentration.




fig 3 5.4 GHz Simulated Gain Plot 3D

Figure 3 illustrates the gain plot of the 5.5 GHz antenna, showing a peak gain of 5.72 dB, adequate for reliable transmission in higher- frequency environments.

Sr. No	Parameter	2.4 GHz	3.7 GHz	5.5GHz
1	S11	-28.45	-17.20	-21.40

		dB	dB	dB
2	VSWR	1.1	1.3	1.7
3	Gain Plot	6.91 dB	6.88 dB	5.72 dB

V. ALGORITHM AND METHODOLOGY

This chapter explains the systematic approach followed in the development of the AI-Powered Adaptive Frequency Antenna System. The methodology includes the hardware setup, signal processing, AI-based antenna selection, and antenna switching mechanism. The goal is to ensure real-time and intelligent selection of the antenna that provides the best communication performance under varying environmental conditions.

Methodology Overview

The proposed system consists of three microstrip patch antennas, each operating at different frequency bands (2.4 GHz, 3.7 GHz, and 5.5 GHz). These antennas are connected through an RF switch/Relay module controlled by a Raspberry Pi. A Software Defined Radio (SDR) module continuously receives wireless signals and sends them to the Raspberry Pi for processing. The Raspberry Pi measures the RSSI, SNR, and other signal quality indicators and runs an AI-based decision algorithm to select the best- performing antenna in real time.

System Workflow

The working process of the system is divided into the following main stages:

1. Signal Reception:

Each antenna receives wireless signals from the communication environment.

2. Signal Monitoring via SDR:

The SDR module digitizes and forwards the received signal data to the Raspberry Pi.

3. Signal Quality Measurement:

The Raspberry Pi extracts metrics such as:

- RSSI (Received Signal Strength Indicator)
- SNR (Signal-to-Noise Ratio)
- Band interference and noise levels

4. AI-Based Decision Making:

The Raspberry Pi uses rule-based or machine learning-based classification to determine which antenna provides the best signal quality.

5. Antenna Switching:

The Raspberry Pi activates the corresponding relay/RF switch to select the best antenna while deactivating others.

6. Continuous Monitoring:

The system runs continuously, updating the antenna selection as signal conditions change.

AI Decision Logic

The system uses either threshold-based logic or a machine learning classifier:

Parameter	Decision Criterion
RSSI	Higher value preferred
SNR	Higher value indicates better signal quality
Interference Level	Lowest value preferred

Decision Formula (Example):

$$Score = \alpha(RSSI) + \beta(SNR) - \gamma(Interference)$$

The antenna with the highest score is selected. Where:

α, β, γ = weight factors determined through experimental tuning.

Hardware Flow Diagram (Explanation)

- Antennas → SDR: Receive RF signals.
- SDR → Raspberry Pi: Converts analog RF to digital signal stream.
- Raspberry Pi → Algorithm: Computes performance metrics.
- Raspberry Pi → Relay Module: Controls switching output pins.
- Relay Module → Antenna: Activates the optimal antenna.

Advantages of the Proposed Methodology

Feature	Benefit
AI-based Switching	Adapts automatically in real-time
SDR Signal Monitoring	Accurate frequency and signal analysis
Relay/RF Switching	Hardware-level

Control	optimization
Multi-band Antenna Setup	Supports various frequency applications
Energy Efficient	Only one antenna active at a time




Fig.4: Block Diagram of System




Fig. 5: Workflow of System

The proposed AI-Powered Adaptive Frequency Antenna system demonstrates effective real-time switching between multi-band antennas based on signal quality. However, there are several opportunities for further enhancement and expansion of the system:

1. Integration with 5G and 6G Networks:

The system can be upgraded to support higher frequency bands such as millimetre-wave frequencies (28 GHz, 38 GHz), making it suitable for next-generation communication technologies.

2. Miniaturization and PCB-Level Integration: The hardware setup can be redesigned into a compact PCB-based module to reduce size and enhance portability for mobile and wearable devices.

3. Use of Deep Learning Algorithms: Advanced AI models such as Deep Neural Networks (DNN) or Reinforcement Learning (RL) can be incorporated for more accurate real-time decision-making and self-learning capabilities.

4. Adaptive Beamforming with Antenna Arrays: The antenna system can be extended into a phased array configuration to enable directional beam steering, improving signal coverage and reducing interference.

5. Cloud and IoT Data Logging:

The system can be connected to cloud servers to store signal analytics, enabling remote monitoring and IoT-based management of wireless communication networks.

7. Industrial and Defence Applications:

With enhancement in accuracy and robustness, the system can be deployed in applications like satellite communication, UAV communication, smart cities, and military-grade wireless networks.

Overall, the system offers a strong foundation for developing future intelligent and autonomously adaptive communication infrastructures.

VI. CONCLUSION

In this project, an AI-Powered Adaptive Frequency Antenna System has been designed and implemented to address the limitations of conventional fixed-frequency antennas. The system utilizes microstrip patch antennas, a Software Defined Radio (SDR) module, and a Raspberry Pi controller to monitor real-time signal parameters such as RSSI and SNR. An AI-based decision algorithm determines the antenna that provides the best performance under current signal conditions, and automatic switching is carried out using a relay/RF switch.

The experimental results and methodology demonstrate that the system successfully adapts to changing wireless environments, providing improved signal stability, reduced interference, and better communication quality. The design is cost-effective, flexible, energy-efficient, and scalable,

making it suitable for modern wireless communication systems such as IoT networks, smart infrastructure, and mobile broadband communication.

Thus, the proposed system provides a smart, reliable, and efficient solution for seamless wireless communication and serves as a foundation for more advanced adaptive antenna technologies in future communication networks.

REFERENCES

1. Y. Li, X. Huang, and Z. Chen, "Adaptive Multi-Band Antenna Design for Modern Wireless Communication Systems," *IEEE Transactions on Antennas and Propagation*, vol. 70, no. 5, pp. 4120–4128, 2022.
2. S. Ahmed and M. Rizwan, "Machine Learning Based Channel Prediction for 5G Networks," *International Journal of Wireless and Mobile Computing*, vol. 14, no. 3, pp. 215–223, 2021.
3. R. Kumar and P. Singh, "Design and Analysis of Tunable Microstrip Patch Antenna Using Varactor Diodes," *International Journal of RF and Microwave Engineering*, vol. 10, no. 4, pp. 45–52, 2020.
4. B. Patel and K. Mehta, "Reconfigurable Antenna Using PIN Diode Switching for Multi-Frequency Operation," *IEEE Access*, vol. 7, pp. 112945–112953, 2019.
5. R. Sharma, A. Gupta, and S. Patel, "SDR Based Real-Time Spectrum Monitoring for Wireless Networks," *International Journal of Electronics and Communication Systems*, vol. 19, no. 2, pp. 105–114, 2021.
6. C. Chen and J. Park, "Reinforcement Learning Algorithm for Autonomous Spectrum Selection in Cognitive Radio Networks," *IEEE Communications Letters*, vol. 27, no. 3, pp. 655–659, 2023.
7. G. Verma and R. B. Patel, "AI-Assisted SDR Framework for Real-Time Frequency Optimization," *Journal of Mobile Networks and Applications*, vol. 27, pp. 268–279, 2022.
8. T. S. Rappaport, *Wireless Communications: Principles and Practice*, 2nd ed. Prentice Hall, 2016.

9. GNU Radio Foundation, "GNU Radio SDR Software Toolkit," Available:
<https://www.gnuradio.org>
10. Raspberry Pi Foundation, "Raspberry Pi Documentation," Available:
<https://www.raspberrypi.org/documentation>