Wajage Aryan Sujit, 2026, 14:5
ISSN (Online): 2348-4098
ISSN (Print): 2395-4752

International Journal of Science, Engineering and Technology
An Open Access Journal

Artificial Intelligence In Vehicle Automation: A Review Of Advanced Driver Assistance Systems, Perception, Sensor Fusion And Safety

Wajage Aryan Sujit[1] Prof. S. S. Bhor[2] Prof. M. C. Kolse[3] Prof. S. K. Said[4]
Department of Artificial Intelligence and Data Science
Jaihind College of Engineering
Pune, Maharashtra, India

Abstract—Advanced Driver Assistance Systems (ADAS) use cameras, radar, LiDAR, ultrasonic sensors and artificial intelligence to monitor a vehicle's surroundings and help drivers avoid crashes. Features such as automatic emergency braking, lane departure warning and lane keeping, adaptive cruise control, blind-spot detection, parking assistance and collision avoidance form the building blocks of vehicle automation, which ranges from basic assistance to highly automated driving. This paper reviews the role of AI in ADAS and vehicle automation. It explains the levels of driving automation, the sensor suite and its trade-offs, and the AI techniques used for lane detection, object detection on camera images and LiDAR point clouds, bird's-eye-view perception and multi-sensor fusion. Evidence on the safety benefits of ADAS features is discussed, together with the difficulty of demonstrating the reliability of highly automated systems. Safety and security engineering, including functional safety, safety of the intended functionality, cybersecurity standards and adversarial attacks on perception, are examined. A layered ADAS architecture covering sensing, perception, fusion and prediction, planning and decision, and control and human–machine interface is proposed, with research gaps, objectives and a comparison of sensors. The review concludes that AI-driven ADAS can greatly reduce road accidents, provided that cost, adverse weather, processing demands and cyber-physical security are addressed.

Index Terms—Advanced driver assistance systems, vehicle automation, autonomous driving, sensor fusion, LiDAR, object detection, automatic emergency braking, automotive safety

I. INTRODUCTION

1. Motivation

Most road crashes involve human error, such as distraction, fatigue, misjudgement or delayed reaction. ADAS aim to compensate for these limitations by continuously watching the road and either warning the driver or intervening automatically. Over the past decade, features that were once limited to luxury cars, such as automatic emergency braking and adaptive cruise control, have become available in mass-market vehicles, including in India where safety ratings increasingly consider them.

AI is at the heart of modern ADAS. Deep learning interprets camera images, detects pedestrians and vehicles, recognizes lane markings and traffic signs, and fuses information from several sensors. As automation increases, AI also predicts the behaviour of other road users and plans the vehicle's actions. Yurtsever *et al.* [1] review the common practices and emerging technologies in automated driving.

This paper reviews the working principles, components, AI techniques, benefits and challenges of ADAS and vehicle automation, and proposes a layered architecture.

2. Objectives Of The Review

The objectives of this review are:

1. 1) To study the working principles and components of ADAS and vehicle automation.

2. 2) To review AI techniques for lane detection, object detection and sensor fusion.

3. 3) To propose a layered ADAS architecture.

4. 4) To compare sensors and analyse the safety benefits of ADAS features.

© 2026 Wajage Aryan Sujit,, ,This is an Open Access article distributed under the terms of the Creative Commons Attribution License (http://creativecommons.org/licenses/by/4.0/), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly credited.

5. 5) To discuss challenges, standards and future scope.

II. OVERVIEW OF KEY CONCEPTS

1. Levels Of Driving Automation

SAE J3016 [2] defines Level 0 (no automation), Level 1 (assistance with steering or speed), Level 2 (combined steering and speed control under driver supervision), Level 3 (conditional automation), Level 4 (high automation within defined conditions) and Level 5 (full automation). Most ADAS on the road today operate at Levels 1 and 2. Fig. 1 classifies common ADAS features.




Fig. 1. Classification of ADAS features.

2. Sensor Suite

Cameras provide rich colour and texture for lane and sign recognition but are sensitive to lighting and weather. Radar measures distance and relative speed reliably in rain and fog but has low resolution. LiDAR produces accurate three-dimensional point clouds but is costly. Ultrasonic sensors serve short-range parking functions.

III. REVIEW OF EXISTING WORK

Lane detection. McCall and Trivedi [3] surveyed video-based lane estimation and presented a robust lane tracking system for driver assistance. Pan *et al.* [4] proposed Spatial CNN, which passes messages between rows and columns of feature maps to capture the long, thin structure of lanes, improving detection when markings are worn or occluded.

Object detection. The KITTI benchmark [5] established standard tasks for stereo, optical flow and 3-D object detection from a sensor-equipped car, and nuScenes [6] added a full 360-degree sensor suite with radar. PointNet [7] learned directly from raw point sets, and PointPillars [8] organized LiDAR points into vertical columns for fast 3-D detection suitable for real-time use.

TABLE I Summary of Literature Survey

Ref.	Authors	Year	Technique Used	Merits	Demerits
[3]	McCall and Trivedi	2006	Video-based lane estimation and tracking	Robust lane tracking for driver assistance	Pre-deep-learning methods
[16]	Koscher et al.	2010	Security analysis of a modern car	Showed control of safety-critical systems	Physical access in early tests
[5]	Geiger et al.	2012	KITTI vision benchmark	Standard tasks for driving perception	Limited weather and scenes
[13]	Kalra and Paddock	2016	Statistical analysis of AV testing	Road testing alone is impractical	Assumes driving-only validation
[12]	Cicchino	2017	Crash-data analysis of FCW and AEB	Substantial reduction in rear-end crashes	US data; specific vehicles
[4]	Pan et al.	2018	Spatial CNN for lanes	Better detection of thin, occluded lanes	Computational cost
[8]	Lang et al.	2019	PointPillars LiDAR detection	Fast 3-D detection from point clouds	Requires LiDAR
[9]	Li et al.	2022	BEVFormer camera transformer	Bird's-eye view from multiple cameras	Heavy computation
[10]	Liu et al.	2023	BEVFusion camera + LiDAR	Improved multi-task fused perception	Sensor calibration needed

Bird's-eye-view and fusion. BEVFormer [9] used transformers to build a bird's-eye-view representation from multiple cameras over time, and BEVFusion [10] fused camera and LiDAR features in a shared bird's-eye view, improving detection and map segmentation. UniAD [11] integrated perception, prediction and planning in one network optimized for the final driving goal.

Safety evidence and reliability. Cicchino [12] analysed police-reported crashes and found that forward collision warning and automatic emergency braking substantially reduced front-to-rear crash rates, with the largest reduction when both were present. Kalra and Paddock [13] showed that demonstrating the safety of autonomous vehicles through road testing alone would require an impractically large number of miles, motivating simulation such as CARLA [14] and formal safety models such as Responsibility-Sensitive Safety [15].

Security. Koscher *et al.* [16] demonstrated that attackers with access to a car's internal network could control braking and other systems, and Eykholt *et al.* [17] showed that small physical stickers on stop signs can cause misclassification by deep networks. Table I summarizes the reviewed literature.

IV. IDENTIFIED RESEARCH GAPS

The following gaps are identified:

1. 1) Perception performance degrades in heavy rain, fog, glare and on poorly marked roads common in India.

2. 2) Datasets rarely represent mixed traffic with two-wheelers, auto-rickshaws, pedestrians and animals.

3. 3) Growing sensor counts and model sizes strain in-vehicle computing and software architecture.

4. 4) Validating rare, safety-critical scenarios remains difficult despite simulation.

5. 5) Cybersecurity of connected and automated vehicles is not yet consistently engineered.

V. SYSTEM ARCHITECTURE

Fig. 2 presents the proposed layered ADAS architecture, which reflects the sense–perceive–plan–act cycle used in vehicle automation.




Fig. 2. Proposed layered ADAS architecture.

1. Sensing Layer

Front and surround cameras, front radar, corner radars, optional LiDAR, ultrasonic sensors, GPS and inertial units provide raw data, together with vehicle signals such as speed and steering angle from the CAN bus.

2. Perception Layer

Neural networks detect lanes, vehicles, pedestrians, cyclists, traffic signs and free space. Each sensor's detections include position, velocity and confidence.

3. Fusion And Prediction Layer

Detections from different sensors are fused into a single object list in a bird's-eye-view frame, tracked over time with filters, and the future trajectories of nearby road users are predicted.

4. Planning And Decision Layer

Feature-specific logic decides actions: maintain set speed and gap for adaptive cruise control, apply corrective steering for lane keeping, or warn and brake for collision avoidance. A safety monitor enforces limits.

5. Control And Hmi Layer

Commands are sent to braking, steering and powertrain controllers. The human–machine interface shows warnings through displays, sounds and haptic feedback, and ensures the driver remains aware of system status.

© 2026 Wajage Aryan Sujit,, ,This is an Open Access article distributed under the terms of the Creative Commons Attribution License (http://creativecommons.org/licenses/by/4.0/), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly credited.

VI. IMPLEMENTATION METHODOLOGY

The automatic emergency braking workflow is shown in Fig. 3. Time to collision with a vehicle ahead is

$$TTC = d / (v_ego - v_lead) \quad (1)$$

where d is the gap and v_ego and v_lead the speeds of the host and lead vehicles. A warning is issued when TTC falls below a first threshold, and autonomous braking begins below a second, smaller threshold. Adaptive cruise control maintains a time gap τ by targeting the distance

$$d_des = d_0 + \tau \cdot v_ego \quad (2)$$

where d_0 is a standstill distance. Kalman filtering combines noisy measurements from radar and camera to estimate object position and velocity.




Fig. 3. Automatic emergency braking workflow.

VII. PERFORMANCE COMPARISON

Table II compares the main sensors. No single sensor is sufficient in all conditions, which is why fusion of complementary sensors is central to reliable ADAS.

TABLE II Comparison of ADAS Sensors

Sensor	Range / Accuracy	Weather Robustness	Cost
Camera	Medium / rich detail	Low (glare, fog)	Low
Radar	Long / good velocity	High	Medium
LiDAR	Medium–long / very accurate 3-D	Medium	High
Ultrasonic	Very short / coarse	High	Very low

VIII. OPEN ISSUES AND FUTURE DIRECTIONS

Table III summarizes the main challenges. Future directions include centralized vehicle computers with software-defined architectures, vehicle-to-everything communication that shares hazard information between cars and infrastructure, end-to-end learned driving with built-in safety checks, India-specific datasets, and compliance with standards such as ISO 26262 [18] for functional safety, ISO 21448 [19] for safety of the intended functionality and ISO/SAE 21434 [20] for cybersecurity.

Challenge	Mitigation
High cost	Camera–radar fusion; scale economies
Adverse weather	Radar fusion; robust training data
Processing demands	Centralized compute; efficient models
Rare scenarios	Simulation; scenario-based testing
Cyber-physical security	ISO/SAE 21434; secure gateways

TABLE III Challenges and Mitigation

IX. CONCLUSION

ADAS and vehicle automation are transforming road safety. The reviewed literature shows that AI-based perception detects lanes, vehicles and pedestrians reliably, that sensor fusion in a bird's-eye-view space improves robustness, and that features such as automatic emergency braking measurably reduce crashes. Significant challenges remain in adverse weather, mixed traffic, processing demands, validation of rare scenarios and cybersecurity. Addressing these through better data, safety engineering and secure architectures will allow ADAS to continue reducing traffic fatalities and support the transition to smarter and safer mobility.

1. Acknowledgment

The authors express their sincere gratitude to the Department of Artificial Intelligence and Data Science, Jaihind College of Engineering, Pune, for providing the facilities, guidance and encouragement needed to carry

out this work. The authors also thank the faculty members and colleagues whose valuable suggestions helped improve the quality of this review.

REFERENCES

1. E. Yurtsever, J. Lambert, A. Carballo, and K. Takeda, "A survey of autonomous driving: Common practices and emerging technologies," IEEE Access, vol. 8, pp. 58443–58469, 2020.
2. SAE International, "Taxonomy and definitions for terms related to driving automation systems for on-road motor vehicles," SAE Standard J3016, 2021.
3. J. C. McCall and M. M. Trivedi, "Video-based lane estimation and tracking for driver assistance: Survey, system, and evaluation," IEEE Trans. Intell. Transp. Syst., vol. 7, no. 1, pp. 20–37, 2006.
4. X. Pan, J. Shi, P. Luo, X. Wang, and X. Tang, "Spatial as deep: Spatial CNN for traffic scene understanding," in Proc. AAAI Conf. Artif. Intell., 2018, pp. 7276–7283.
5. A. Geiger, P. Lenz, and R. Urtasun, "Are we ready for autonomous driving? The KITTI vision benchmark suite," in Proc. IEEE CVPR, 2012, pp. 3354–3361.
6. H. Caesar et al., "nuScenes: A multimodal dataset for autonomous driving," in Proc. IEEE/CVF CVPR, 2020, pp. 11621–11631.
7. C. R. Qi, H. Su, K. Mo, and L. J. Guibas, "PointNet: Deep learning on point sets for 3D classification and segmentation," in Proc. IEEE CVPR, 2017, pp. 652–660.
8. A. H. Lang et al., "PointPillars: Fast encoders for object detection from point clouds," in Proc. IEEE/CVF CVPR, 2019, pp. 12697–12705.
9. Z. Li et al., "BEVFormer: Learning bird's-eye-view representation from multi-camera images via spatiotemporal transformers," in Proc. ECCV, 2022, pp. 1–18.
10. Z. Liu et al., "BEVFusion: Multi-task multi-sensor fusion with unified bird's-eye view representation," in Proc. IEEE ICRA, 2023, pp. 2774–2781.
11. Y. Hu et al., "Planning-oriented autonomous driving," in Proc. IEEE/CVF CVPR, 2023, pp. 17853–17862.
12. J. B. Cicchino, "Effectiveness of forward collision warning and autonomous emergency braking systems in reducing front-to-rear crash rates," Accid. Anal. Prev., vol. 99, pp. 142–152, 2017.
13. N. Kalra and S. M. Paddock, "Driving to safety: How many miles of driving would it take to demonstrate autonomous vehicle reliability?" Transp. Res. Part A, vol. 94, pp. 182–193, 2016.
14. A. Dosovitskiy, G. Ros, F. Codevilla, A. Lopez, and V. Koltun, "CARLA: An open urban driving simulator," in Proc. 1st Conf. Robot Learn. (CoRL), 2017, pp. 1–16.
15. S. Shalev-Shwartz, S. Shammah, and A. Shashua, "On a formal model of safe and scalable self-driving cars," arXiv:1708.06374, 2017.
16. K. Koscher et al., "Experimental security analysis of a modern automobile," in Proc. IEEE Symp. Security Privacy, 2010, pp. 447–462.
17. K. Eykholt et al., "Robust physical-world attacks on deep learning visual classification," in Proc. IEEE/CVF CVPR, 2018, pp. 1625–1634.
18. International Organization for Standardization, "Road vehicles—Functional safety," ISO 26262:2018, 2018.
19. International Organization for Standardization, "Road vehicles—Safety of the intended functionality," ISO 21448:2022, 2022.
20. ISO/SAE, "Road vehicles—Cybersecurity engineering," ISO/SAE 21434:2021, 2021.