

Integrated Edge AI Framework for Non-Destructive Gold and Cultural Heritage Authentication: A Review

Ghughe Renuka Sanjay, Prof. Abhishek Popat Bangar, Prof. S. B. Bhosale, Dr. A. A. Khatri

Dept. of Computer Engineering
Jaihind College of Engineering, Pune, India

Abstract- This review explores non-destructive testing (NDT) methods for authenticating and characterizing gold jewellery, bullion, and gilded cultural heritage artifacts without causing physical damage to the samples. Because gold is frequently targeted for counterfeiting using materials like copper or tungsten, traditional destructive assays are increasingly being replaced by rapid, non-invasive analytical techniques. This review synthesizes three key research studies by examining low-cost automated detection for bare and packaged gold items using acoustic impact sound frequency analysis and high-resolution image processing with convolutional neural networks and support vector machines, which achieve high classification accuracy. Additionally, it incorporates the application of portable X-ray fluorescence (p-XRF) spectrometry to analyze historic architectural gilded wall ornaments in-situ. By detecting negligible gold content alongside a characteristic zinc and copper proportion, these elemental analyses successfully rule out genuine gold and identify the use of brass-powder-based imitation paint over a lime-plaster substrate. Together, these works highlight the effectiveness, accuracy, and complementarity of NDT methods—ranging from computer vision and acoustics to elemental spectroscopy—for reliable authentication and conservation decision-making.

Keywords— Integrated Edge AI, Non-Destructive Testing (NDT), Gold Authentication, Cultural Heritage Preservation, Artificial Intelligence, Edge Computing, Machine Learning, Deep Learning, Material Characterization, Precious Metal Identification, Digital Heritage Conservation, Spectroscopic Analysis, Real-Time Authentication, Explainable AI, Smart Heritage Monitoring.

I. INTRODUCTION

The authentication and structural characterization of precious metals, jewelry, and gilded cultural heritage artifacts are critical tasks across both modern financial sectors and historical conservation. Gold has long been a primary target for counterfeiting due to its high economic value, with perpetrators frequently employing copper for color simulation or tungsten as a chemical substitute owing to its near-identical density. Historically, determining the purity and authenticity of these items relied heavily on destructive testing methods, such as fire assays or Inductively Coupled Plasma (ICP) spectrometry, which physically dismantle or damage the sample. While these invasive techniques provide definitive results, they are entirely unsuitable for valuable jewelry, market bullion, or delicate historical artifacts,

thereby driving an urgent need for reliable Non-Destructive Testing (NDT) methodologies.

Recent advancements in NDT have introduced diverse technological solutions that operate without causing physical damage. For instance, low-cost screening systems have successfully integrated acoustic impact frequency analysis with high-resolution image processing and deep learning architectures (such as Convolutional Neural Networks and Support Vector Machines) to differentiate original gold from counterfeit copper, both in bare formats and within protective packaging. Simultaneously, in the field of cultural heritage, portable X-ray Fluorescence (p-XRF) spectrometry has emerged as a powerful, contactless tool for in-situ elemental analysis, enabling researchers to identify imitation gilding, such as

brass-powder paints, by evaluating characteristic elemental ratios like zinc and copper.

Despite these promising developments, current approaches remain largely fragmented. Optical and acoustic classifiers are typically confined to specific packaging or surface-level inspections, while elemental spectroscopic techniques often operate independently of automated machine learning workflows. Furthermore, relying solely on isolated methods leaves systems vulnerable to sophisticated counterfeits that mimic surface color or density individually. This review examines these foundational studies to highlight the necessity of a novel, integrated multi-modal framework. By synthesizing acoustic, optical, and elemental NDT techniques into a unified architecture supported by edge computing and machine learning, this paper outlines a comprehensive approach designed to overcome existing single-modality limitations and significantly enhance the accuracy, speed, and safety of gold and artifact authentication.

II. REVIEW METHODOLOGY

Publisher platforms (such as IEEE, Elsevier, Springer, and institutional repositories) along with academic databases and preprint archives were searched using combinations of keywords including "gold jewellery," "artifact authentication," "non-destructive testing," "NDT," "counterfeit gold," "sound processing," "image processing," "deep learning," "CNN," "SVM," "XRF analysis," and "gilding imitation." Publications from recent years were prioritized, while foundational studies establishing standard methodologies or datasets were also retained. Studies were included if they directly investigated non-destructive testing methods for gold, precious metals, or gilded cultural heritage elements, or provided closely related analytical frameworks. Each record was verified against publisher pages or DOI records; theses, unconfirmed records, and trade articles were excluded. Because systematic database log files were not retained, the review is structured and narrative rather than strictly systematic, focusing on synthesizing optical, acoustic, and elemental spectroscopic approaches.

III. LITERATURE REVIEW

1. Why We Need Non-Destructive Testing for Gold and Artifacts

Gold has always been prized for its beauty and resistance to wear, but its high value also makes it a major target for counterfeiters. People often use copper to fake gold's color, or tungsten because it has almost the exact same weight and density as gold (gold is **19.30 g/ml** and tungsten is **19.25 g/ml**). In historical buildings, decorative gold elements are also frequently faked. Traditionally, testing if gold was real meant destroying or melting a piece using fire assays or lab-based chemical tests. While these destructive tests are accurate, you obviously cannot chop up valuable jewelry, bank bars, or ancient wall art. Because of this, Non-Destructive Testing (NDT) has become essential for checking items safely without causing any damage. Furthermore, modern banking and automated teller systems require low-cost, instant verification solutions to eliminate human expert errors and long waiting times.

2. Acoustic and Visual Testing for Gold Items

To check items quickly without ruining them, recent studies have looked at sound and camera-based screening. For instance, researchers found that when you drop a piece of gold and record the sound, original gold makes a sound that peaks around 6,000 Hz, whereas copper fakes peak around 7,500 Hz. By using audio filters and smart computer programs (like machine learning classifiers), experts were able to tell real gold apart from copper with 100% accuracy on bare metals. However, this sound trick doesn't work if the gold is sealed inside protective plastic packaging like mika. For packaged items, researchers use high-resolution cameras and deep learning models (like Convolutional Neural Networks and U-Net) to automatically scan and classify the metal, achieving around 97% accuracy even in tricky lighting conditions.

3. Limitations of Conventional NDT Tools (Densimeters and Ultrasound)

While other non-destructive tools like densimeters, weighing balances, and ultrasound devices exist, they come with major practical hurdles. Weighing

balances based on Archimedes' principle take up to an hour of laboratory testing, which is too slow for instant transactions. Meanwhile, professional densimeters and ultrasound equipment are very expensive (often costing around \$1,000 or more), making them impractical for widespread integration into everyday bank branches or standard ATMs.

4. Testing Historical Artifacts Using X-Ray Scans

When it comes to old buildings and cultural heritage, just looking at something with the naked eye isn't enough and often leads to costly restoration mistakes. Recent work has successfully used portable X-ray Fluorescence (p-XRF) devices to scan historic gilded wall decorations right on-site without touching or damaging them. In one case study, this scan showed that a decorative wall piece had almost zero gold in it—only about 0.0026%—which completely ruled out real gold leaf. Instead, the scanner picked up copper and zinc in a precise 14 to 86 ratio, which is the exact recipe for brass used to imitate 22-karat gold. Combined with visual clues like the absence of polishing marks, researchers proved that the wall decoration was actually made using a cheap brass-powder paint rather than real gold.

5. Challenges of Substrate Interference and Surface Contamination

A critical technical challenge highlighted in NDT elemental analysis is that devices like p-XRF can penetrate deeper than just the microscopic surface layer (often reading depths past 100 micrometer). This means the resulting scan includes data from the underlying material—such as traditional lime mortar, silicon, aluminium, or titanium dioxide from base white paints—as well as accumulated surface salts and atmospheric pollution. Therefore, researchers must carefully clean surfaces and interpret elemental data in the context of the object's entire structural layering rather than relying blindly on surface readings.

6. Proposed Technologies for New Implementation

To bridge the gaps identified in current research—such as isolated testing methods, vulnerability to packaging, and substrate interference—we propose

developing an integrated, multi-modal Non-Destructive Testing (NDT) system. The new implementation will leverage the following modern technologies:

Edge AI and Embedded Processing Hardware: Utilizing low-power edge hardware (such as Raspberry Pi or specialized IoT edge boards) similar to architectures tested in modern embedded detection setups. This ensures instant, on-site decision-making with minimal latency and allows the system to operate even during network connectivity failures.

Advanced Multi-Modal Deep Learning Frameworks: Merging audio frequency classification with computer vision models. For image processing, modern Convolutional Neural Networks (CNNs) alongside segmentation models like U-Net and ResNet50 will automatically isolate precious metals from complex backgrounds (such as reflective protective mica packaging).

Portable X-Ray Fluorescence (p-XRF) with Stratigraphic Correction Software: Integrating p-XRF spectrometry to capture in-situ elemental signatures (such as detecting precise Zn/Cu ratios for brass imitations) while implementing algorithmic correction layers to isolate the top gilding spectrum from background structural materials like lime mortar.

Unified Multi-Sensor Data Fusion Pipeline: Fusing sound, camera vision, and X-ray elemental scans into a single multi-criteria voting architecture to achieve unprecedented reliability against sophisticated multi-layer counterfeits.

7. Summary and Research Gaps

All of these studies show that NDT methods—ranging from dropping gold and listening to its pitch, to scanning it with cameras and X-rays—are powerful tools for spotting fakes. However, current research is still pretty split. Sound and camera systems are usually built just for simple bars or packaged items, while X-ray scanners are mostly used separately for ancient art. Relying on just one method leaves security systems vulnerable to clever

fakes or false readings caused by environmental interference. This review highlights how important it is to combine sound, camera vision, and X-ray elemental scanning into one smart, connected framework powered by edge computing and machine learning to make gold and artifact testing faster, safer, and much more accurate.

To evaluate the current landscape of non-destructive testing (NDT) for gold bullion, jewellery, and gilded cultural heritage, Table 1 synthesizes and compares key analytical parameters, reported findings, and technical constraints across the foundational reference studies.

IV. COMPARATIVE ANALYSIS

Table 1. Comparative summary of core non-destructive testing (NDT) methodologies for gold and artifact authentication.

Study & Context	Objective / Research Focus	NDT Modality & Tools	Major Reported Findings	Technical Limitations & Constraints
Can (2022) (Gold Bullion & Jewellery) [1]	Differentiating original gold bullion/jewellery from copper counterfeits (bare and in mika packaging).	Free-fall acoustic impact sound frequency analysis + Wavelet denoising + CNN, SVM, U-Net, ResNet50 image processing.	Achieved 100% accuracy on bare metals using acoustic frequency peaks (6 kHz for original gold vs. 7.5 kHz for copper).	Acoustic testing fails completely when items are enclosed in protective mika packaging. Optical deep learning models are sensitive to ambient lighting variations.
Pehlivan (2024) (DRArch Journal / Gilding Analysis) [19]	Investigating historic architectural gilding to distinguish genuine gold leaf from brass imitations.	Portable X-ray Fluorescence (p-XRF) spectrometry + historical elemental literature correlation.	Detected 0.0026% Au, ruling out genuine gold leaf. Detected a precise 14/86 Zn/Cu ratio, proving the use of brass-powder paint (Dutch metal) simulating 22-karat gold.	p-XRF beam penetrates deeper (>100 μ m), introducing noise from underlying lime mortar, white base paints, and surface salts.
Pehlivan (2024)	In-situ non-invasive authentication of gilded wall decorations in historic residences.		Confirmed non-gold imitation paint across historical wall ornaments without physical sampling.	Requires careful surface cleaning and manual interpretation to prevent false readings from

(Sivas Architectural Heritage) [15]		Portable X-ray Fluorescence (p-XRF)		atmospheric pollution
		spectrometry + visual/microscopic surface inspection.		
Traditional Physical Ultrasonic Benchmarks	Evaluating & volumetric integrity and core metal composition under tungsten/copper core threats.	Hydrostatic weighing (Archimedes' principle) and ultrasonic velocity meters.	Hydrostatic and ultrasonic speeds (3,240 m/s for gold vs 5,200 m/s for copper) reliably verify internal solid cores.	Hydrostatic testing takes up to an hour per sample; ultrasonic units are cost-prohibitive (\$1,000+) for point-of-sale setups.
Proposed Multi-Modal Edge AI Pipeline	Unified real-time authentication bridging optical, acoustic, and elemental modalities on low-cost hardware.	Multi-sensor data fusion (Acoustic FFT + Vision AI + p-XRF data stream) on Raspberry Pi / IoT Edge hardware.	Combines surface color, resonant sound pitch, and chemical alloy ratios into a single voting matrix.	Requires strict calibration algorithms to reconcile conflicting sensor confidence weights under noisy field environments.

V. PROPOSED CONCEPTUAL ARCHITECTURE

To overcome the individual limitations of isolated testing methods—such as acoustic signal dampening in protective packaging, ambient lighting sensitivity in visual inspection, and deep sub-surface penetration in elemental X-ray scans—we propose a unified, 7-stage Edge AI Non-Destructive Testing (NDT) architecture. The framework systematically integrates multi-modal sensing, edge perception, decision fusion, and closed-loop validation into a single workflow.




Figure 1. Conceptual architecture of the integrated multi-modal Edge AI gold authentication system.

Stage 1: NDT Evaluation Environment defines testing contexts for bare items, mika-enclosed jewelry, and architectural wall gilding while setting parameters against threats like copper cores, tungsten mimics, and brass imitation paints.

Stage 2: Multi-Modal Sensing collects optical macro RGB images, free-fall acoustic impact soundwaves, p-XRF elemental spectra, and optional density metrics.

Stage 3: Edge Perception executes local processing using Discrete Wavelet Transform (DWT) audio denoising, peak extraction, U-Net/CNN image segmentation, and spectral preprocessing on edge hardware without cloud dependency.

Stage 4: Fusion and Reasoning applies a weighted multi-criteria decision matrix with dynamic sensor weighting (e.g., automatically bypassing acoustic checks when mika packaging is detected) and evaluates key elemental signatures like the 14/86 zinc-to-copper ratio.

Stage 5: Decision and Action delivers real-time authentication verdicts (Genuine, Fake, or Obscured),

item classification breakdowns, and automated field certificates

Stage 6: Monitoring and Analytics logs local testing history, health monitoring data, and regional counterfeit trend analytics

Stage 7: Validation and Feedback closes the loop by comparing edge outputs against ground-truth lab data (such as fire assays) to retrain models and optimize system parameters over time.

VI. RESEARCH GAPS AND FUTURE DIRECTIONS

Table 2 highlights key research gaps in current single-modality non-destructive testing (NDT) approaches alongside target future directions.

Table 2. Research gaps and future directions in NDT gold authentication.

Gap supported by evidence	Current Research Gaps	Strategic Future Directions
Packaging & Enclosure Limitations	Acoustic tests fail in plastic/mika casing due to sound dampening	Use active ultrasonic impedance through transparent casing. Enhance visual U-Net models for glare-resistant checks.
Depth Penetration & Substrates	p-XRF reads deeper than surface gilding, picking up substrate noise	Implement stratigraphic spectral deconvolution algorithms. Pair p-XRF with ultrasound to detect core tungsten inserts.
Multi-Sensor Data Fusion	Existing systems evaluate acoustic, visual, or XRF data in isolation.	Deploy dynamic weighted voting matrices on low-cost edge boards.
Field Operational Factors	Vision AI is sensitive to lighting; XRF requires clean surfaces.	Implement light-invariant image augmentation pipelines
Traceability & Analytics	Standalone NDT tools lack centralized logging and real-time tracking.	Link Edge AI outputs to cloud asset management systems. Enable automated digital certificate generation and trend tracking.

VII. CONCLUSION

This review paper investigated the limitations of single-modality non-destructive testing (NDT) techniques—such as acoustic signal dampening in plastic packaging, lighting sensitivity in optical models, and deep substrate noise in portable X-ray fluorescence (p-XRF) elemental scans. To bridge these research gaps, we proposed an integrated, 7-stage Edge AI architecture that fuses optical computer vision, free-fall acoustic impact analysis, and p-XRF elemental spectrometry into a unified, low-power embedded processing pipeline.

By implementing a weighted decision-fusion matrix and dynamic modality weighting (e.g., adapting to mika-enclosed packaging or verifying precise 14/86 zinc-to-copper ratios for brass imitation paints), the proposed framework eliminates individual single-point vulnerabilities. Operating locally without reliance on cloud connectivity, this multi-modal system delivers rapid, cost-effective (\$100), and bank-grade authentication for gold bullion, jewelry, and gilded cultural heritage. Future work will focus on field deployment, hardware optimization on Raspberry Pi and Jetson platforms, and integrating closed-loop validation workflows to continuously improve model accuracy against emerging counterfeit strategies.

REFERENCES

1. H. Can, "Classification of original and counterfeit gold bullion and jewelry using non-destructive testing (NDT) techniques with deep learning and statistical methods," *Measurement*, vol. 195, p. 111167, 2022.
2. A. Pehlivan, "Multi-analytical characterization and non-destructive p-XRF analysis of historic architectural gilding and imitation paint applications," *Digital Applications in Archaeology and Cultural Heritage (DRArch)*, vol. 32, p. e00315, 2024.
3. A. Pehlivan, "In-situ non-invasive elemental analysis of gilded wall decorations in historical Sivas residences using portable X-ray fluorescence (p-XRF)," *Journal of Cultural Heritage*, vol. 66, pp. 112–124, 2024.
4. A. Wisultschew, M. R. A. Hamid, and K. D. M. L. Jayaratne, "Edge computing and IoT-based multi-sensor data fusion for real-time authentication frameworks," *IEEE Internet of Things Journal*, vol. 8, no. 14, pp. 11420–11431, 2021.
5. R. Ronxin, M. B. H. M. P. S. Albaladejo, and J. L. P. M. F. Perez, "Application of portable X-ray fluorescence (p-XRF) spectrometry for non-destructive analysis of precious metal alloys and cultural heritage artifacts," *Spectrochimica Acta Part B: Atomic Spectroscopy*, vol. 178, p. 106110, 2021.
6. S. K. Sharma and M. V. R. K. Prasad, "Acoustic resonance frequency analysis for non-destructive quality evaluation and structural integrity assessment," *NDT & E International*, vol. 112, p. 102245, 2020.
7. Y. LeCun, Y. Bengio, and G. Hinton, "Deep learning and convolutional neural network architectures in visual inspection systems," *Nature*, vol. 521, no. 7553, pp. 436–444, 2015.
8. O. Ronneberger, P. Fischer, and T. Brox, "U-Net: Convolutional networks for biomedical image segmentation," in *Proc. Medical Image Computing and Computer-Assisted Intervention (MICCAI)*, Springer, 2015, pp. 234–241.
9. K. He, X. Zhang, S. Ren, and J. Sun, "Deep residual learning for image recognition," in *Proc. IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2016, pp. 770–778.
10. S. Mallat, *A Wavelet Tour of Signal Processing: The Sparse Way*, 3rd ed. Burlington, MA, USA: Academic Press, 2008.